Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

DIGITAL INSULATION TESTER

DIT-2500

Up to 2500 V · 50 GΩ · True-RMS multimeter · CAT III 1000 V / CAT IV 600 V

01 KEY SPECIFICATIONS

INSULATION TEST	100 / 250 / 500 / 1000 / 2500 V
IR RANGE	Up to 50 GΩ (at 2500 V)
DAR / PI	Built-in · 15 s / 30 s / 1 min / 10 min
MULTIMETER	True-RMS · AC/DC to 1500 V
SAFETY	CAT III 1000 V · CAT IV 600 V
POWER	Li-ion 3.7 V × 2, rechargeable



DIT-2500 · INSULATION TESTER

02 TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
INSULATION RESISTANCE RANGE, BY TEST VOLTAGE	
100 V	0.1 MΩ – 2 GΩ
250 V	0.25 MΩ – 5 GΩ
500 V	0.5 MΩ – 10 GΩ
1000 V	1 MΩ – 20 GΩ
2500 V	2.5 MΩ – 50 GΩ
INSULATION TEST	
Accuracy	±(3% + 5) to 399.9 MΩ · ±(5% + 5) 0.4–2 GΩ · ±(10% + 5) 2.001–50 GΩ
Open-circuit voltage	90% – 110% of rated
Short-circuit current	≥ 1 mA
DAR	1 min : 15 s and 1 min : 30 s
PI	10 min : 60 s
MULTIMETER (TRUE-RMS)	
DC voltage	6 V – 600 V ±(0.5% + 5) · 1500 V ±(1% + 5)
AC voltage	6 V – 600 V ±(1.2% + 5) · 1500 V ±(2% + 5), 40 Hz – 1 kHz
Resistance	600 Ω – 60 MΩ
Capacitance	10 nF – 100 mF
Frequency	10 Hz – 20 kHz (ACV 1 – 600 V)
Diode / continuity	Diode test · buzzer below approx. 50 Ω
GENERAL	
Safety category	CAT III 1000 V / CAT IV 600 V
Terminals	LINE, EARTH, GUARD (insulation) · VΩ, COM (multimeter, max. 1500 V)
Battery	Li-ion 14500, 3.7 V × 2, rechargeable
Operating temperature	0 – 40 °C, below 75% RH
Dimensions (L × W × H)	189 × 89 × 55 mm
Weight	Approx. 380 g (incl. battery)
Warranty	12 months against manufacturing defects only

03 APPLICATIONS

- Insulation resistance: motors, transformers, cables
- DAR / PI insulation quality assessment
- Switchgear, panel and cable commissioning

04 WHAT'S IN THE BOX

✓ Test leads ✓ Charging set ✓ Instruction manual

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - DIT-2500 Product Catalogue.