Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

RELAY TEST SET · PORTABLE TROLLEY

# RTS-5A

0–200 A (6 V / 50 V) · AC or DC voltage output · digital timer

## 01 KEY SPECIFICATIONS

| | |
|---|---|
| CURRENT OUTPUT | 0–200 A, 7 ranges |
| VOLTAGE OUTPUT | 0–230 V AC / 0–240 V DC |
| TIMER | 0–9.999 s / 0–99.99 s, ±1% |
| INPUT | 230 V, 1 phase, 50 Hz |
| METERING | Digital ammeter & voltmeter |
| CONSTRUCTION | Portable trolley, single unit |



RTS-5A · RELAY TEST SET

## 02 TECHNICAL SPECIFICATIONS

| PARAMETER | SPECIFICATION |
|---|---|
| **INPUT & OUTPUT** | |
| Input | 230 V, single phase, 50 Hz A.C. |
| Current Output | 0–1/5/10/20A at 6V or 50V; 0–50/100/200A at 6V - continuously variable |
| AC Voltage Output | Continuously variable 0–230 V A.C., 240 VA max |
| DC Voltage Output | Continuously variable 0–240 V D.C., 240 VA (not simultaneous with AC) |
| **TIMING & METERING** | |
| Timer | 0–9.999 sec or 0–99.99 sec, ±1% accuracy |
| Current Meter | Digital, 0–5A A.C. basic range, 0–100% scaled, ±2% of full range |
| Voltage Meter | Digital, 0–500 V A.C./D.C., ±2% of full range |
| Measuring CT | Multi-ratio wound primary CT, ratio 1-5-10-20-50-100-200 A/5A |
| **GENERAL** | |
| Construction | Portable trolley-type, single unit, top-hinged lid |
| Mains Cable | 2 metres, 3-pin plug |
| Warranty | 12 months against manufacturing defects only |

## 03 APPLICATIONS

- Protective relay testing and commissioning
- Over-current and earth fault relay testing
- Circuit breaker and tripping coil testing
- Field and laboratory relay calibration

## 04 WHAT'S IN THE BOX

- ✓ Operation manual
- ✓ Schematic circuit diagram
- ✓ Works test report



All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - RTS-5A Product Catalogue.