Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

DIGITAL EARTH RESISTANCE TESTER

# DET-2000

4-terminal · earth resistance & soil resistivity · 3½-digit LCD

## 01 KEY FEATURES

- 4-terminal design
- Earth resistance and soil resistivity
- 3½-digit LCD, Lo-Bat indicator
- Rechargeable Ni-Cd battery
- Rugged ABS body, handheld or bench-top

Testing kit (spikes, cables, hammer) available at extra cost - not included standard.




DET-2000 · DIGITAL EARTH RESISTANCE TESTER

## 02 TECHNICAL SPECIFICATIONS

| PARAMETER | SPECIFICATION |
|---|---|
| **MEASUREMENT** | |
| Terminals | 4-terminal (E1, P1, P2, E2) |
| Display | 3½-digit LCD, with Lo-Bat indicator |
| Accuracy | ±3% (0–10%, 90–100%); ±1.5% (10–90% of range) |
| Range Configuration | Dual and triple range - see table below |
| **TEST & SAFETY** | |
| High Voltage Test | 2kV A.C. r.m.s., 1 min, circuit to containing case |
| Insulation Resistance Test | More than 25 MΩ at 500V D.C. |
| **GENERAL** | |
| Power | Rechargeable Ni-Cd cells, 230 V/50 Hz charging cord |
| Dimensions (L×W×H) | 172 × 98 × 38 mm |
| Weight | Approx. 575 g |
| Warranty | 12 months against manufacturing defects only |

## 03 AVAILABLE RANGES (Ω)

| DUAL RANGE | TRIPLE RANGE |
|---|---|
| 0–5–500 | 0–5–50–500 |
| 0–10–100 | 0–10–100–1000 |
| 0–20–200 | 0–20–200–2000 |
| 0–10–1000 | |
| 0–20–2000 | |
| 0–200–2000 | |

*Any other range can be manufactured against specific requirements.*

## 04 APPLICATIONS

- Earth resistance testing - power, telecom, railway
- Domestic and industrial installation earthing checks
- Soil resistivity surveys for electrode positioning
- General non-inductive/non-capacitive resistance testing

## 05 WHAT'S IN THE BOX

- ✓ Carrying case
- ✓ Charging cord
- ✓ Instruction manual



All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - DET-2000 Product Catalogue.