Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

DIGITAL CLAMP MULTIMETER · TRUE-RMS AC/DC

# DCM 5410 TR

True-RMS AC/DC clamp multimeter · capacitance · frequency · temperature

## 01 KEY FEATURES

- True-RMS AC and DC current
- Low-Z ACV
- NCV and live-wire test
- Capacitance, frequency and temperature
- Auto-ranging 6000-count LCD
- Inrush current and low-pass filter ACV



DCM 5410 TR · DIGITAL CLAMP MULTIMETER

## 02 TECHNICAL SPECIFICATIONS

| PARAMETER | SPECIFICATION |
|---|---|
| **CURRENT** | |
| AC Current Ranges | 60 A / 600 A / 1000 A (True-RMS) |
| DC Current Ranges | 60 A / 600 A / 1000 A |
| Current Accuracy | ±(4.0% + 10) AC and DC; AC response 50 Hz – 60 Hz |
| Jaw Opening (Max.) | 40 mm |
| **VOLTAGE & RESISTANCE** | |
| DC Voltage | 600 mV / 6 V / 60 V / 600 V / 1000 V |
| AC Voltage (True-RMS) | 6 V / 60 V / 600 V / 750 V |
| Low Impedance ACV | 6 V / 60 V / 300 V - ≤3 KΩ input |
| Voltage Accuracy | DC ±(0.5% + 7) to 60 V, ±(1.0% + 10) above<br>AC ±(1.0% + 10) to 60 V, ±(1.0% + 12) above |
| Low-Pass Filter ACV (V.F.C) | 40 Hz – 200 Hz, ±(5.0% + 10), for VFD outputs |
| Resistance | 600Ω / 6KΩ / 60KΩ / 600KΩ / 6MΩ / 20MΩ / 60MΩ |
| **OTHER MEASUREMENTS** | |
| Capacitance | 1 nF – 10 mF (8 ranges) |
| Frequency | 10 Hz – 10 MHz, ±(0.3% + 3); duty cycle 10% – 90% |
| Temperature | –20°C to 1000°C / –4°F to 1832°F (supplied probe: –20°C to 250°C) |
| **DISPLAY & SAFETY** | |
| Display | 6000 Counts LCD, auto-ranging |
| NCV / Live Wire Test | Provided |
| Safety Category | CAT III 600 V |
| **GENERAL** | |
| Power Supply | 2×AAA 1.5V Batteries |
| Dimensions (L×W×H) | 230 × 75 × 40 mm |
| Weight (incl. battery) | Approx. 313 g |
| Warranty | 12 months against manufacturing defects only |

## 03 APPLICATIONS

- AC and DC current measurement on panels and boards
- Solar and battery system diagnostics (DC clamp)
- Electrical maintenance and switchgear testing
- Combined electrical and temperature diagnostics

## 04 WHAT'S IN THE BOX

- ✓ Test leads
- ✓ K-type temperature probe
- ✓ Carrying pouch
- ✓ User manual
- ✓ 2×AAA batteries



All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - DCM 5410 TR Product Catalogue.