Cambridge Instruments
& Engg. Co.

EST. 1963 · HOWRAH, INDIA

PHASE SEQUENCE INDICATOR · ABS MOULDED

PSI-2

Phase sequence indicator · compact ABS body · panel or handheld use

01 KEY FEATURES

- Compact ABS moulded body
- Panel-mount or handheld use
- RYB / RBY phase rotation check



PSI-2 · PHASE SEQUENCE INDICATOR

02 TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
ELECTRICAL	
Operating Voltage (Horizontal)	50–500 V AC
Operating Voltage (Vertical)	100–500 V AC
Frequency	25–60 Hz
Rating	30 seconds at 500 V
Burden	15 VA at 500 V
GENERAL	
Body	ABS moulded
Dimensions	96 × 96 × 45 mm
Important	Not to be left in the circuit
Accessories	Carrying case and test leads (supplied)
Warranty	12 months against manufacturing defects only

03 APPLICATIONS

- 3-phase phase sequence check
- Switchboard commissioning
- Motor connection verification

04 WHAT'S IN THE BOX

✓ Carrying case ✓ Test leads

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - PSI-2 Product Catalogue.