Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

DIGITAL MULTIMETER · TRUE-RMS, MANUAL RANGING

# DM 321T

True-RMS · 3½-digit · manual ranging · hFE · capacitance · backlit

ISO 9001:2015 CERTIFIED

## 01 KEY FEATURES

- True-RMS AC measurement
- 3½-digit backlit display
- Data hold
- Auto-ranging capacitance
- hFE transistor test
- Protective holster




DM 321T · DIGITAL MULTIMETER

## 02 TECHNICAL SPECIFICATIONS

| PARAMETER | SPECIFICATION & ACCURACY |
|---|---|
| **DISPLAY & RANGING** | |
| Measurement Type | True-RMS |
| Ranging | Manual |
| Display | 3½-digit with backlight |
| **VOLTAGE & CURRENT** | |
| DC Voltage | 200 mV / 2 V / 20 V / 200 V / 1000 V \| ±(0.5% rdg + 3 digits) |
| AC Voltage (True-RMS) | 2 V / 20 V / 200 V / 750 V \| ±(0.8% rdg + 5 digits) @ 40 Hz–1 kHz |
| DC Current | 200 µA / 2 mA / 20 mA / 200 mA / 20 A \| ±(0.8% rdg + 10 digits) |
| AC Current (True-RMS) | 20 mA / 200 mA / 20 A \| ±(1.0% rdg + 15 digits) @ 40 Hz–400 Hz |
| **OTHER MEASUREMENTS** | |
| Resistance | 200Ω / 2KΩ / 20KΩ / 200KΩ / 2MΩ / 20MΩ \| ±(0.8% rdg + 3 digits) |
| Capacitance (Auto Ranging) | 6 nF – 20 mF \| ±(3.5% rdg + 20 digits) |
| Transistor Test | hFE |
| Additional Functions | Continuity, diode test, REL, AC mains frequency test (750 V range), data hold, backlight, auto power-off, low battery |
| **GENERAL** | |
| Power Supply | 2 × AA battery |
| Dimensions (L×W×H) | 178 × 86 × 52 mm |
| Weight | Approx. 360 g (incl. battery & holster) |
| Warranty | 12 months against manufacturing defects only |

## 03 APPLICATIONS

- General electrical maintenance and panel testing
- Accurate AC measurement on non-sinusoidal loads (True-RMS)
- Basic electronic troubleshooting incl. transistor testing

## 04 WHAT'S IN THE BOX

✓ Test leads ✓ User manual ✓ Battery ✓ Holster



All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - DM 321T Product Catalogue.