Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

INSULATION TESTER · MOTOR-CUM-HAND DRIVEN

CIE/777 HM Range Guide

ISO 9001:2015 CERTIFIED

Mains motor with hand-crank backup

Every standard voltage and range

230 V mains motor or hand crank, rated voltages 500, 1,000, 2,500, 5,000 and 10,000 V. Pick the rated test voltage first, then the insulation resistance range that suits your equipment. Each combination below is a standard build.

5	14	500–10,000
RATED VOLTAGES	STANDARD RANGES	VOLTS



CIE/777 HM · ILLUSTRATIVE IMAGE

01 STANDARD RANGES BY RATED VOLTAGE

RATED VOLTAGE	INSULATION RESISTANCE RANGE (MΩ)
500 V	0–1,000
1,000 V	0–2,000
2,500 V	0–5,000 · 0–10,000 · 0–20,000
5,000 V	0–5,000 · 0–10,000 · 0–20,000 · 50–50,000 · 100–100,000
10,000 V	0–10,000 · 0–20,000 · 50–50,000 · 100–100,000

Ranges shown are the standard builds. Any other range can be manufactured against specific requirements.

02 COMBINING VOLTAGES AND RANGES

Dual voltage & dual insulation range

Two rated voltages, each with its own range. The selected range must lie within the rated resistance listed for that voltage. Not available for 10,000 V.

Single voltage, dual insulation range

One rated voltage with two insulation ranges within the listed rated resistance for that voltage. Not available for 10,000 V.

Dual voltage, single insulation range

Two rated voltages sharing one insulation range within the listed rated resistance. Not available for 10,000 V.

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - CIE/777 HM Range Guide.

INSULATION TESTER · MOTOR-CUM-HAND DRIVEN

CIE/777 HM Range Guide

ISO 9001:2015 CERTIFIED

Multi-range options, specifications, accessories and ordering

03 MULTIRANGE SERIES: CIE/777 HM/MR

SERIES	RATED VOLTAGE	INNER SCALE (MΩ)	OUTER SCALE (MΩ)
MR-A	5,000 V 2,500 V 1,000 V	0–5,000 0–2,500 0–1,000	50–100,000 25–50,000 10–20,000
MR-B	5,000 V 2,500 V 1,000 V	0–2,000 0–1,000 0–500	10–10,000 5–5,000 2–2,000
MR-C	5,000 V 2,500 V	100–100,000 50–50,000	Single scale Single scale
MR-D	5,000 V 2,500 V	0–5,000 0–2,500	50–100,000 25–50,000
MR-E	5,000 V 2,500 V 1,000 V	50–50,000 25–25,000 10–10,000	Single scale Single scale Single scale

Multirange instruments carry a range selector switch, so one instrument covers every voltage and range listed in its series. Any other configuration can be built to order.

04 KEY SPECIFICATIONS

Drive	**Mains motor (230 V, 50 Hz A.C.) plus collapsible hand-crank backup**
Body	**Seasoned wooden cabinet with sunmica finish, detachable lid, handle, lock**
Scale Length	**100 mm (approx.)**
Accuracy	**As per IS: 2992-1987**
Dimensions (incl. top cover, approx.)	**14 × 10 × 10 inch**
Weight (incl. top cover)	**12 kg (approx.)**
Response Time	**3 seconds**

05 SUPPLIED AND OPTIONAL

Supplied as standard

- ✓ Mains cord, 2 m
- ✓ 1 pair of H.V. testing leads

Optional, at extra cost

- Carrying case
- 15-minute timer facility
- Testing leads, 1 m or 2 m
- Additional / special-grade H.V. testing leads, 2 m

06 HOW TO ORDER

To order, quote the **model**, the **rated voltage** and the **insulation range**, for example **`CIE/777 HM, 500 V / 0–1,000 MΩ`**. Any range not listed can be manufactured against specific requirements - enquire.

cieinstruments@gmail.com · +91 98300 91260 · +91 98300 92117

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - CIE/777 HM Range Guide.