Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

RELAY TEST SET · SINGLE PHASE

# RTS-5

Secondary current injection relay test set · digital timer · digital metering

ISO 9001:2015 CERTIFIED

## 01 KEY FEATURES

- Continuously variable current output
- Timer starts on energising, stops on relay actuation
- Digital ammeter and voltmeter
- NO / NC contact selector
- Alternative voltage output



RTS-5 · RELAY TEST SET

## 02 TECHNICAL SPECIFICATIONS

| PARAMETER | SPECIFICATION |
|---|---|
| **INPUT & OUTPUT** | |
| Input | 230 V, single phase, 50 Hz A.C. |
| Current Output | 0–1/2/5/10/20A at 14V or 4V; 0–50/100/200A at 4V |
| Output Voltage (alternative) | 0–240 V A.C. at 1 A (mutually exclusive with current) |
| Fixed Voltages | 50 V & 110 V A.C. at 1 A |
| Duty | Intermittent - 5 min ON / 10 min OFF |
| Cooling | Air natural |
| **TIMING & METERING** | |
| Timer | 9.999 sec (1ms res.) or 99.99 sec (10ms res.) |
| Ammeter | Rectangular multi-range digital, 0–1/2/5/10/25/50/100/200A |
| Voltmeter | Rectangular A.C., 0–300 V |
| **GENERAL** | |
| Warranty | 12 months against manufacturing defects only |

## 03 APPLICATIONS

- Protective and over-current relay testing
- Earth fault relay testing
- Relay commissioning and maintenance in substations and panels



All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - RTS-5 Product Catalogue.