Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

INSULATION TESTER · MOTOR OPERATED

CIE/777

Mains-motor driven insulation tester

Direct-reading insulation resistance testing

A universal, multi-purpose instrument for checking insulation and conductance under simulated operating conditions in high-tension electrical and electronic fields. The dielectric absorption test needs the voltage applied for several minutes, and driving the instrument by motor makes this easy. Polarisation index is the resistance after 10 minutes divided by the resistance after 1 minute, and better results come from longer test periods. The high sensitivity of the instrument gives sensible readings in these tests, and it can run for hours when locating intermittent shorts, defective electrical connections and insulation or conductor failure.



CIE/777 · ILLUSTRATIVE IMAGE

14	5	3 s
STANDARD RANGES	RATED VOLTAGES	RESPONSE TIME

STANDARD RATED TEST VOLTAGES

500 V · 1,000 V · 2,500 V · 5,000 V · 10,000 V

01 HIGHLIGHTS

- ✓ Operated from 230 V, 50 Hz A.C. mains
- ✓ Anti-parallax mirror scale with knife-edge pointer
- ✓ Guard ring around the line terminal, plus a guard terminal
- ✓ ON-OFF switch, jewel lamp for mains ON, safety fuse
- ✓ Accurate, quick response (3 seconds)
- ✓ Seasoned wooden cabinet with sunmica finish, detachable lid, carrying handle and lock
- ✓ Highly sensitive cross-coil indicator
- ✓ Externally accessible infinity adjuster
- ✓ Terminals accept 4 mm plug and spade terminations
- ✓ Conforms to IS 2992:1987

02 TYPICAL APPLICATIONS

- Sustained insulation and polarization index (PI) testing on large motors and generators
- Power transformer insulation assessment including dielectric absorption ratio
- HV cable and switchgear insulation testing
- Substation commissioning by EPC contractors

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - CIE/777 Long-Form Catalogue.

03 HOW IT WORKS

PRINCIPLE

A mains-driven motor turns the generator, and a static rectifier supplies the D.C. test voltage to a cross-coil ohm meter.

CONSTRUCTION

Housed in a seasoned wooden cabinet with sunmica finish, complete with a detachable lid, carrying handle and lock. Terminals are designed to accommodate standard cable terminations, including 4 mm plug and spade.

04 SALIENT FEATURES

Mains motor drive

A built-in motor for 230 V, 50 Hz A.C. mains, with a static rectifier and a cross-coil ohm meter. The test voltage can be applied for as long as the test needs.

Guard ring and guard terminal

A guard ring around the line terminal and a guard terminal eliminate errors due to surface leakage. An externally accessible infinity adjuster is also provided.

Safe, simple controls

A highly insulated panel carries an ON-OFF switch, a jewel lamp indicating mains ON and a safety fuse protecting the motor, with a 3-pin socket and a 2 m supply cord.

Quick response

3 seconds, when a resistance equal to the central scale mark is suddenly inserted between the terminals, as per IS 2992:1987.

05 TECHNICAL SPECIFICATIONS

Drive	Mains motor, 230 V, 50 Hz A.C.
Body	Seasoned wooden cabinet with sunmica finish, detachable lid, handle, lock
Scale Length	100 mm (approx.)
Accuracy	As per IS: 2992-1987
High Voltage Test	Min. 2 kV or (rated voltage + 1) kV A.C. (r.m.s.), 1 min
Insulation Resistance Test	Better than 50 MΩ at 500 V D.C.
Guard Terminal & Infinity Adjuster	Guard ring and guard terminal eliminate surface-leakage errors; externally accessible infinity adjuster provided
Dimensions (incl. top cover, approx.)	14 × 10 × 10 inch
Weight (incl. top cover)	9 kg (approx.)
Response Time	3 seconds
Warranty	12 months against manufacturing defects only

Ranges are listed on the following pages. Specifications are approximate where marked.

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - CIE/777 Long-Form Catalogue.

06 STANDARD RANGES BY RATED VOLTAGE

RATED VOLTAGE	INSULATION RESISTANCE RANGE (MΩ)
500 V	0–1,000
1,000 V	0–2,000
2,500 V	0–5,000 · 0–10,000 · 0–20,000
5,000 V	0–5,000 · 0–10,000 · 0–20,000 · 50–50,000 · 100–100,000
10,000 V	0–10,000 · 0–20,000 · 50–50,000 · 100–100,000

Ranges shown are the standard builds. Any other range can be manufactured against specific requirements.

07 COMBINING VOLTAGES AND RANGES

Dual voltage & dual insulation range

Two rated voltages, each with its own range. The selected range must lie within the rated resistance listed for that voltage. Not available for 10,000 V.

Single voltage, dual insulation range

One rated voltage with two insulation ranges within the listed rated resistance for that voltage. Not available for 10,000 V.

Dual voltage, single insulation range

Two rated voltages sharing one insulation range within the listed rated resistance. Not available for 10,000 V.

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - CIE/777 Long-Form Catalogue.

08 MULTIRANGE SERIES: CIE/777/MR

SERIES	RATED VOLTAGE	INNER SCALE (MΩ)	OUTER SCALE (MΩ)
MR-A	5,000 V	0–5,000	50–100,000
	2,500 V	0–2,500	25–50,000
	1,000 V	0–1,000	10–20,000
MR-B	5,000 V	0–2,000	10–10,000
	2,500 V	0–1,000	5–5,000
	1,000 V	0–500	2–2,000
MR-C	5,000 V	100–100,000	Single scale
	2,500 V	50–50,000	Single scale
MR-D	5,000 V	0–5,000	50–100,000
	2,500 V	0–2,500	25–50,000
MR-E	5,000 V	50–50,000	Single scale
	2,500 V	25–25,000	Single scale
	1,000 V	10–10,000	Single scale

Multirange instruments carry a range selector switch, so one instrument covers every voltage and range listed in its series. Any other configuration can be built to order.

09 SUPPLIED AND OPTIONAL

Supplied as standard

- ✓ Mains cord, 2 m
- ✓ 1 pair of H.V. testing leads

Optional, at extra cost

- Rexine carrying case
- 15-minute timer facility
- Testing leads, 1 m or 2 m
- Additional / special-grade H.V. testing leads, 2 m

10 HOW TO ORDER

To order, quote the **model**, the **rated voltage** and the **insulation range**, for example **CIE/777, 500 V / 0–1,000 MΩ**. Any range not listed can be manufactured against specific requirements - enquire.

cieinstruments@gmail.com · +91 98300 91260 · +91 98300 92117 · cieinstruments.in

11 WARRANTY AND SUPPORT

WARRANTY AND SUPPORT

Every CIE instrument carries a 12-month warranty against manufacturing defects only. After-sales support is handled directly by CIE, not through a distributor network.

OFFICE

55, Ezra Street, 4th Floor
Yamuna Bhawan
Kolkata 700001, West Bengal

WORKS

23/2, Maulana Abul Kalam Azad Road
Howrah 711101, West Bengal

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - CIE/777 Long-Form Catalogue.