VAR TECH®
Quality • Reliability • Economy

Smart Clamp Multimeters
V 2001+ & V 2002+

Features

- 3 5/6 Digits (6000 Counts)
- 6 / 60 A / 200 A AC (V 2001+)
- 600mA / 6 A / 60 A AC (V 2002+)
- 6 A / 60 A DC (V 2002+)
- 1000 / 750 V DC/AC
- True RMS, Fully Auto
- Cap., Temp., Measurements
- Freq., Measurements (V 2002+ only)
- Data Hold, Continuity & Diode Test
- A.P.O., NCV & Live Wire Test
- Rechargeable battery - Type C



ISO 9001

SPECIFICATIONS			
		V 2001+	**V 2002+ (Leakage Tester)**
DC Voltage	Range	600 mV, 6 V, 60 V, 600 V, 1000 V	
	Basic Accuracy	± (0.5 % reading + 3 digits)	
AC Voltage (True RMS)	Range	6 V, 60 V, 600 V, 750 V	
	Basic Accuracy	± (0.8 % rdg. + 3 digits)	
AC Current (True RMS)	Range	6 A / 60 A / 200 A	600 mA / 6 A / 60 A
	Accuracy	± (2 % rdg. + 30 digits)	± (4 % rdg. + 20 digits) - 200~600mA
DC Current	Range	-	6 A / 60 A
	Accuracy	-	± (2 % rdg. + 30 digits)
Resistance	Range	600 Ω, 6 K Ω, 60 K Ω, 600 K Ω, 6 M Ω, 60 M Ω	
	Basic Accuracy	± (0.8% rdg. + 5 digits)	
Capacitance Test		6 nF,60 nF, 600 nF, 6 µF, 60 µF, 600 µF, 6 mF & 60 mF.	
Frequency / D. Cycle		-	6 Hz ~ 10 MHz. Max. I/P - 250V.
Temperature Measurement		-20 ~ 1000 ºC (-4 ~ 1832 ºF).	
Other Facilities / Features		N.C.V. Test, Live Wire Test, Diode Test, Continuity Test, Display Brightness Adjustment, Auto Power Off, Low Batt. Indication & Data Hold. REL. (V 2002+ Only).	
Accessories Supplied		Test Leads - Pair, Temp., Probe, Carrying Pouch, User Manual & Battery Charging Cable.	
Dimension & Weight		170 x 64 x 26 mm & Approx. 150 gms. (Incl. Batt.).	

** All Specifications & appearances are subject to change without prior notice*