VAR TECH®
Quality • Reliability • Economy

Digital Clamp Multimeter
V 266+ & V 266 C

Features

- 3 ¾ Digits (4000 Counts) - V 266+
- 3 ⅚ Digits (6000 Counts) - V 266C
- Manual Ranging
- 600 V AC/DC
- 1000 A AC
- V 266 C Only - Back Light, Cap., Freq., & Temp., Measurements
- Torch
- NCV, Diode & Continuity Test
- Superior Quality



SPECIFICATIONS			
		V 266+	**V 266 C**
DC Voltage	Range	4V / 40V / 600V	60mV / 600 mV / 6V / 60V / 600V
	Basic Accuracy	± (0.8 % reading + 2 digits)	
AC Voltage	Range	4V / 40V / 600V	600 mV / 6V / 60V / 600V
	Basic Accuracy	± (1 % rdg. + 10 digits)	
AC Current	Range	40A / 400A / 1000A	60A / 400A / 1000 A
	Accuracy	± (2.5 % rdg. + 10 digits)	
Resistance	Range	400 Ω, 4 K Ω, 40 K Ω, 400 K Ω, 4 M Ω, 40 M Ω	600 Ω, 6 K Ω, 60 K Ω, 600 K Ω, 6 M Ω, 60 M Ω
	Basic Accuracy	± (1.2% rdg. + 2 digits)	
Capacitance Test		-	60 nF, 600 nF, 6 µF, 60 µF, 600 µF, 6 mF & 60 mF.
Frequency Meas. (in ACV Range)		-	10 Hz ~ 1 KHz.
Temperature Measurement		-	
Other Facilities / Features		N.C.V. Test, Diode Test, Continuity Test, Torch, Low Batt. Indication & Data Hold. Back Light (V 266C Only).	
Accessories Supplied		Test Leads - Pair, Carrying Pouch, User Manual & Battery (1.5V×2 – AAA - Optional). Temp. Probe (V 266C Only).	
Dimension & Weight		222 x 90 x 35 mm & Approx. 220 gms. (Incl. Batt.).	

** All Specifications & appearances are subject to change without prior notice*