VAR TECH®
Quality • Reliability • Economy

Programmable D.C. Power Supply
PPS-3005-3 (Multi O/P)

Features

- **Single Output – High Precision**
- **Linear Type – Very Reliable**
- 2 Independent + 1 Fixed O/P
- 0 ~ 30 V, 0 ~ 5 x 2 O/P
  2.5 / 3.3 / 5 V, 3 A Fixed O/P
- With P.C. Interface (USB)
- Auto CV and CC switch
- High Resolution : 100mV/10mA
- Smart cooling fan
- High Stability & Accuracy
- Save & Recall of 4 Panel Settings
- Panel Lock & O/P On/Off



ISO 9001 CE HEAVY DUTY

Model		PPS-3003-3	PPS-3005-3
Main O/P - Ch. 1 & 2		0~30V / 0~3A	0~30V / 0~5A
Aux. (Fixed) O/P		2.5 / 3.3 / 5 V, 3 A	
Constant voltage operation (Main O/P)			
Line regulation		≤0.01%+3mV	
Load regulation		≤0.01%+3mV (I ≤ 3A) & ≤0.01%+3mV (I ≥ 3A)	
Ripple & Noise		≤ 1 mV rms (I ≤ 3A) ≤ 2 mV rms (I ≥ 3A) (5Hz~1MHz)	
Constant current operation (Main O/P)			
Line regulation		≤0.2%+3mA	
Load regulation		≤ 0.2% + 3 mA (I ≤ 3A) & ≤ 0.2% + 5 mA (I ≥ 3A)	
Ripple & Noise		≤ 3 mA (I ≤ 3A) & ≤ 6 mA (I ≥ 3A)	
Display			
Voltmeter / Ammeter		5 digits & 4 digits LED display	
Setting Accuracy	Voltage	± (0.5% + 2 Dgts.)	
	Current	± (0.5% + 2 Dgts.) (I ≤ 3A) & ± (0.5% + 5 Dgts.) (I ≥ 3A)	
Reading Accuracy	Voltage	± (0.5% + 2 Dgts.)	
	Current	± (0.5% + 3 Dgts.) (I ≤ 3A) & ± (0.5% + 5 Dgts.) (I ≥ 3A)	
Protection		Over load, over voltage, over current and reverse polarity	
Panel lock		Provided	
Prog. / Interface		USB Optional. Supports Labview.	
Memory		4 sets	
Oper. Environment		0℃~40℃, ≤80%RH	
Power source		AC 110 V / 220 V (± 10%) selectable, 50 / 60 Hz.	
Dimensions & Weight		250 x 150 x 310 mm. 7.5 Kg & 10 Kg.	
Accessories		Power cord x1, Operation manual x1. Optional : USB Cable x1, Software C.D. x1	

** All Specifications & appearances are subject to change without prior notice*