VAR TECH®
Quality • Reliability • Economy

Auto Ranging D.C. Power Supply
PPSA-100W-8005 S

Features



- **Programmable Power supply**
- **Auto Ranging**
- 0~80V, 0~5A Max 100W Power
- Remote Sensing
- 4 Digits display each for Voltage & Current
- New Generation, New Technology
- Slim Design, Advanced DC Power supply
- Switching type - Having High Accuracy
- High Resolution : 10 mV / 1 mA
- High Stability, Low Ripple & Noise
- With P.C. Interface (RS232 & RS485)
- Output ON/OFF function
- Constant Power mode
- Data Record facility
- Multiple protections: OVP, OCP, OTP

ISO 9001 CE

Auto-range power supply allows wider voltage and current output than a conventional power supply.

User friendly & Easy to use.

** All Specifications & appearances are subject to change without prior notice*

VAR TECH®
Quality • Reliability • Economy

Auto Ranging D.C. Power Supply
PPSA-100W-8005 S

Specifications :

Rated Output	Voltage	0.5~81V
	Current	0~5.1A
	Power	100W
	Power ratio	4.131
	OVP	0.5~88V
	OCP	0.1~5.5A
Line regulation	Voltage	≤0.01%+3mV
	Current	≤0.1%+5mA
Load regulation	Voltage	≤20mV
	Current	≤10mA
Setting accuracy	Voltage	≤0.05% +10mV
	Current	≤0.2% +2mA
Reading accuracy	Voltage	≤0.05% +10mV
	Current	≤0.2% +2mA
Setting resolution	Voltage	10mV
	Current	1mA
Reading resolution	Voltage	10mV
	Current	1mA
Ripple & Noise (20Hz-20MHz)	Voltage	≤10mVrms
	Current	≤8mArms
Rise time	Empty load	≤300ms
	Full load	≤300ms
Fall time	Empty load	≤500ms
	Full load	≤200ms
Max compensation voltage		2V
Recovery time		≤5ms (50% load change)
Efficiency		80% typical
Power factor		0.9 typical
Protection		Over voltage, over current and over temperature protections
Standard Interface		RS232 & RS485 interface, Support SCPI & ModBus-RTU commands
Optional interface		USB, LAN
External trigger		Through 2-pin terminal on rear panel
Memory		100x4 memories (100 groups, 4 memories in each group)
Withstanding voltage		I/P-FG: 2KVAC/min ≤5mA
Insulation		O/P-FG: 500VDC >100MΩ
Operating environment		0~40℃, ≤80%
Storage environment		-10℃~70℃, ≤70%RH
Power source		AC 100V~240V, 47~63Hz
Accessories		Power cord x1, Operation manual x1, RS232 cable x1, Software CD x1
Dimension		55Wx140Hx315D mm
Weight		1.8kg

** All Specifications & appearances are subject to change without prior notice*