VAR TECH®
Quality • Reliability • Economy

Signal Generator (DDS F.G. + Arbitrary)
SGDA-15M & SGDA-30M

Features

- SGDA-15M : 15 MHz
- SGDA-30M : 30 MHz
- Dual Channel with P.C. Interface
- 2.4” TFT Color LCD Display
- With Built-In Frequency Counter
- Superior Quality Product
- 60 Arbitrary Waveforms



ISO 9001

Specifications :

MODEL > >		SGDA-15M	SGDA-30M
Frequency Output (0.01 μ Hz Resolution)		15 MHz - Sine, Square & Triangle. 6 MHz - Pulse, TTL & Arbitrary.	30 MHz - Sine. 25 MHz Square & Triangle. 6 MHz - Pulse, TTL & Arbitrary.
Output Channels		2 Channels	
Sampling Rate		266 MSa/S (Vertical Resolution - 14 Bits)	
Waveforms		Sine, Square, Pulse (Adjustable Duty Cycle, Precise Adjustment of Pulse Width & Period), Triangular Wave, Partial Sine Wave, CMOS Wave, DC Level (Set DC Amplitude By Adjusting Offset), Half Wave, Full Wave, Positive Staircase Wave, Anti-Ladder Wave, Noise Wave, Exponential Rise, Exponential Drop, Multisonic Wave, Symplectic Pulse, Lorenz Pulse & 60 Arbitrary Waveforms.	
Amplitude	Sine Wave	Frequency ≤ 11 MHz : 2mVpp ~ 20Vpp. Frequency ≥ 11 MHz : 2mVpp ~ 10Vpp.	
	Square Wave & Triangle Wave	Frequency ≤ 10 MHz : 2mVpp ~ 20Vpp. Frequency ≥ 10 MHz : 2mVpp ~ 5Vpp.	
Freq. Meas. & M.F. Counter		Frequency Range : 1 Hz ~ 100 MHz.	
Other Functions / Facilities		D.C. Offset, Sweep (Lin. / Log.), Burst & Settings Store/Recall	
Display		2.4” TFT LCD	
Interface		USB & TTL Ext.	
Accessories		Power Adaptor, User Manual (Printed / C.D. / Download QR Code), S/W (Printed / C.D. / Download QR Code), USB Cable & BNC Cables.	
Power source		DC 5V (±0.5V) - Adaptor for 220 V AC (±10%) / 50 Hz (± 3 Hz) Provided.	

** All Specifications & appearances are subject to change without prior notice*