VAR TECH®
Quality • Reliability • Economy

Bench Top L.C.R. Meter
LCR-1B

Features



- Large 3.5” Colour LCD Display
- With Adjustable Backlight
- 5 Digit Display (Primary & Secondary)
- **10Hz~10KHz Continuously Adjustable (1Hz steps)**
- **Automatic identification of component type**
- Fast Measurement Speed : 10 Times per Second
- High Stability, Auto / Locked Range
- Support DC Resistance & Electrolytic Capacitance Measurement
- RS 232 & USB Optional. Supports SCPI Protocol & Labview
- Handler interface for automatic sorting
- Data Recording Function

ISO 9001 CE

Specifications :

Test Parameters	L / C / R / Z & X / D / Q / θ / ESR. Basic Accuracy : 0.1%	
Test Frequencies	10 Hz ~ 10 KHz Continuously adjustable in 1 Hz steps	
Display Digits	5 Digits for both Primary and secondary display	
Measurement Range	L	2 µH – 9999 H
	C	2 pF – 9999 µF
	R	2 Ω - 99.99MΩ
Measurement Speed	Fast : 10, Medium : 5, Slow : 2 (Times / Second)	
Internal Bias	0 mV ~ 1500 mV, Adjustable in 1 mV steps	
Test Level (V_{rms})	100 mV ~ 2000 mV Level, Continuously Adjustable in 1 mV steps	
Correction Functions	Open / Short	
Measurement Terminals	Five Terminals	
Comparator	5 Gear Sorting : 3 Qualified, 1 Failed & 1 Ancillary.	
Interface (Optional)	Handler, RS 232 & USB.	
Power Supply	220 V AC (±10%), 50 Hz (± 5%), ≤ 10W.	
Environment	0 ~ 40 °C, R.H. < 80%.	
Accessories	User’s Manual, Mains Cord & 4 Terminal Kelvin Test Leads.	
Weight & Dimensions (W x H x D)	Approx. 2.3 Kgs., 265 mm x 105 mm x 305 mm	

** All Specifications & appearances are subject to change without prior notice*