VAR TECH®
Quality • Reliability • Economy

# Bench Top L.C.R. Meter
# LCR-2A

## Features




- Large 3.5” Colour LCD Display
- With Adjustable Backlight
- 5 Digit Display
  (Primary & Secondary)
- **100Hz~10KHz**
  **Adjustable in 10 Steps**
- **Automatic identification of component type**
- Fast Measurement Speed : 10 Times per Second
- High Stability, Auto / Locked Range
- Support DC Resistance & Electrolytic Capacitance Measurement
- RS 232 & USB Optional. Supports SCPI Protocol & Labview
- Handler interface for automatic sorting
- Data Recording Function

ISO 9001 CE

### Specifications :

| | | |
|---|---|---|
| **Test Parameters** | L / C / R / Z & X / D / Q / θ / ESR. Basic Accuracy : 0.1% | |
| **Test Frequencies** | 100 Hz / 120 Hz / 200 Hz / 400 Hz / 800 Hz<br>1 KHz / 2 KHz / 4 KHz / 8 KHz / 10 KHz | |
| **Display Digits** | 5 Digits for both Primary and secondary display | |
| **Measurement Range** | L | 0.001µH - 9999H |
| | C | 0.001pF - 9999µF |
| | R | 0.0001Ω - 99.99MΩ |
| **Measurement Speed** | Fast : 10, Medium : 5, Slow : 2 (Times / Second) | |
| **Internal Bias** | 0 mV ~ 1500 mV, Adjustable in 1 mV steps | |
| **Test Level ($V_{rms}$)** | 100 mV / 300 mV / 600 mV / 1000 mV / 1500 mV / 2000 mV | |
| **Correction Functions** | Open / Short | |
| **Measurement Terminals** | Five Terminals | |
| **Comparator** | 5 Gear Sorting : 3 Qualified, 1 Failed & 1 Ancillary. | |
| **Interface (Optional)** | Handler, RS 232 & USB. | |
| **Power Supply** | 220 V AC (±10%), 50 Hz (± 5%), ≤ 10W. | |
| **Environment** | 0 ~ 40 °C, R.H. < 80%. | |
| **Accessories** | User’s Manual, Mains Cord & 4 Terminal Kelvin Test Leads. | |
| **Weight & Dimensions (W x H x D)** | Approx. 2.3 Kgs., 265 mm x 105 mm x 305 mm | |

** All Specifications & appearances are subject to change without prior notice*