VAR TECH®
Quality • Reliability • Economy

Smart Digital Multimeter - V 92 S

Features

- 3 5/6 Digits (6000 Counts)
- Auto Ranging / Auto Range Detection
- True RMS
- Primary & Secondary Display
- Input Jack Prompt & Burnt Fuse Prompt
- Auto Ranging Cap., Freq., & Temp., Tests
- A.P.O., NCV, D/H, B/L & Torch
- A/V Continuity & Diode Test with Holster



SPECIFICATIONS		
DC Voltage	Range	600 mV, 6 V, 60 V, 600 V
	Basic Accuracy	± (0.5 % rdg + 3 digits)
AC Voltage (True RMS)	Range	6 V, 60 V, 600 V
	Basic Accuracy	± (1 % rdg + 3 digits).
DC Current	Range	600 mA, 6 A, 10 A
	Basic Accuracy	± (1.2 % rdg + 3 digits)
AC Current (True RMS)	Range	600 mA, 6 A, 10 A
	Basic Accuracy	± (1.2 % rdg + 3 digits).
Resistance	Range	600 Ω, 6 K Ω, 60 K Ω, 600 K Ω, 6 M Ω, 60 M Ω
	Basic Accuracy	± (1 % rdg + 5 digits)
Capacitance	Range	6 nF, 60 nF, 600 nF, 6 µF, 60 µF, 600 µF, 6 mF, 60 mF
	Accuracy	± (3.5 % rdg + 20 digits)
Frequency	Range	6 Hz, 60 Hz, 600 Hz, 6 KHz, 60 KHz, 600 KHz, 6 MHz, 10 MHz
	Basic Accuracy	± (1 % rdg + 3 digits)
Temperature	Range	- 40 ºC ~ 1000 ºC (-40 ºF ~ 1832 ºF)
Other Facilities / Features		NCV, Torch, ACV Freq., Measurement, A/V Continuity Test, Diode Test, LCD Back Light, Data Hold, Auto Power Off, Low Batt., Ind., Jack & Burnt Fuse Prompt, Intelligent Mode.
Accessories Supplied		Holster (Installed), Test Leads, User Manual, Battery - 4 x AAA (Installed / Kept Aside) - Optional & Temperature Probe.
Dimension & Weight		146 x 72 x 50 mm & Approx. 235 gms. (With Batt. & Holster)

** All Specifications & appearances are subject to change without prior notice*