Cambridge Instruments
& Engg. Co.

EST. 1963 · HOWRAH, INDIA

INSULATION TESTER · MULTIRANGE, METAL BODY

CIE/444/MR

Multirange insulation tester · selectable voltage · built-in continuity range

01 KEY FEATURES

- Selectable multi-voltage operation
- Built-in continuity range
- Anti-magnetic aluminium, die-cast body



CIE/444/MR · INSULATION TESTER

MR-5 to MR-8 are wooden-body only (see **CIE/666/MR**) - not available in this metal-body configuration.

02 OPTIONAL ACCESSORIES (extra cost)

+ Carrying case
+ Test leads, 1m
+ H.V. test leads, 2m (general)
+ H.V. test leads, 2m (special)

03 TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
Body	Anti-magnetic aluminium
Generator Type	Hand-driven
Series Available (Metal Body)	MR-1 to MR-4 only
Continuity Range	Built-in as standard on all MR series
Warranty	12 months against manufacturing defects only

Any configuration apart from the standard MR series above is available on request.

04 AVAILABLE SERIES - VOLTAGE, RANGE & CONTINUITY

SERIES	VOLTAGE & RESISTANCE RANGES	CONTINUITY RANGE
MR-1	1000V/0–2000MΩ · 500V/0–1000MΩ · 250V/0–500MΩ	0–20 KΩ
MR-2	1000V/0–200MΩ · 500V/0–100MΩ · 250V/0–50MΩ	0–1 KΩ
MR-3	500V/0–1000MΩ · 250V/0–500MΩ · 100V/0–200MΩ	0–5 KΩ
MR-4	500V/0–100MΩ · 250V/0–50MΩ · 100V/0–20MΩ	0–1 KΩ

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - CIE/444/MR Product Catalogue.