Cambridge Instruments
& Engg. Co.

EST. 1963 · HOWRAH, INDIA

INSULATION TESTER · MOTOR-CUM-HAND OPERATED

# CIE/777 HM

## 10000 V / 50–50000 MΩ

Insulation tester · motor + hand-crank backup · sustained PI / DAR

## 01 KEY FEATURES

- Motor drive with hand-crank backup
- Sustained PI & DAR testing (motor mode)
- Centrifugal governor (hand mode)
- Collapsible generator handle
- Guard terminal & infinity adjuster

## 02 WHAT'S IN THE BOX

✓ Mains cord, 2 metres
✓ 1 pair of H.V. testing leads

## 03 OPTIONS & ACCESSORIES (extra cost)

+ Carrying case
+ 15-minute timer facility
+ Test leads 1m/2m; special H.V. leads 2m
+ Dual voltage & range option
+ Single voltage, dual range option




CIE/777 HM · INSULATION TESTER · ILLUSTRATIVE IMAGE

## 04 TECHNICAL SPECIFICATIONS

| PARAMETER | SPECIFICATION |
|---|---|
| **CONFIGURATION** | |
| Rated Test Voltage | 10000 V D.C. |
| Insulation Resistance Range | 50–50000 MΩ |
| **DRIVE & MEASUREMENT** | |
| Drive | Mains motor (230V, 50Hz A.C.) + collapsible hand-crank |
| Scale Length | 100 mm (approx.) |
| Accuracy | As per IS: 2992-1987 |
| Response Time | 3 seconds |
| Guard Terminal & Infinity Adjuster | Guard ring & guard terminal eliminate surface-leakage errors; infinity adjuster provided |
| **TEST & SAFETY** | |
| High Voltage Test | Min. 2kV or (rated V + 1)kV A.C. r.m.s., 1 min |
| Insulation Resistance Test | Better than 50 MΩ at 500V D.C. |
| **GENERAL** | |
| Body | Seasoned wooden cabinet, sunmica finish, detachable lid, handle, lock |
| Dimensions (top cover) | 14 × 10 × 10 inch (approx.) |
| Weight (top cover) | 12 kg (approx.) - vs 9 kg for plain CIE/777 |
| Warranty | 12 months against manufacturing defects only |

*Dual-voltage, dual-range options and custom ranges are available against specific requirements - enquire.*



ISO 9001:2015 CERTIFIED

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - CIE/777 HM 10000 V, 50-50000 MΩ Product Catalogue.