Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

DIGITAL INSULATION TESTER

DIT-2500

Insulation tester + True-RMS multimeter · DAR / PI · CAT III / CAT IV

01 KEY FEATURES

- True-RMS multimeter
- Built-in DAR & PI with selectable timer
- Live test-voltage display
- LED high-voltage output indicator
- Backlit LCD, data hold, auto power-off
- Rechargeable Li-ion batteries

02 WHAT'S IN THE BOX

✓ Test leads ✓ Charging set ✓ Instruction manual



DIT-2500 · INSULATION TESTER

03 TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
INSULATION RESISTANCE RANGE, BY TEST VOLTAGE	
100 V	0.1 MΩ – 2 GΩ
250 V	0.25 MΩ – 5 GΩ
500 V	0.5 MΩ – 10 GΩ
1000 V	1 MΩ – 20 GΩ
2500 V	2.5 MΩ – 50 GΩ
INSULATION TEST	
Accuracy	±(3%+5) to 399.9 MΩ · ±(5%+5) 0.4–2 GΩ · ±(10%+5) 2.001–50 GΩ
Open-circuit voltage	90% – 110% of rated
Short-circuit current	≥ 1 mA
DAR	1 min : 15 s and 1 min : 30 s
PI	10 min : 60 s
MULTIMETER (TRUE-RMS)	
DC voltage	6 V – 600 V ±(0.5% + 5) · 1500 V ±(1% + 5)
AC voltage	6 V – 600 V ±(1.2% + 5) · 1500 V ±(2% + 5), 40 Hz – 1 kHz
Resistance	600 Ω – 60 MΩ
Capacitance	10 nF – 100 mF
Frequency	10 Hz – 20 kHz (ACV 1 – 600 V)
Diode / continuity	Diode test · buzzer below approx. 50 Ω
GENERAL	
Safety category	CAT III 1000 V / CAT IV 600 V
Terminals	LINE, EARTH, GUARD (insulation) · VΩ, COM (multimeter)
Battery	Li-ion 14500, 3.7 V × 2, rechargeable
Operating temperature	0 – 40 °C, below 75% RH
Dimensions (L × W × H)	189 × 89 × 55 mm
Weight	Approx. 380 g (incl. battery)
Warranty	12 months against manufacturing defects only

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - DIT-2500 Product Catalogue.