Cambridge Instruments
& Engg. Co.

EST. 1963 · HOWRAH, INDIA

PHASE SEQUENCE INDICATOR · ABS MOULDED

# PSI-2

Phase sequence indicator · compact ABS body · panel or handheld use

## 01 KEY FEATURES

- Compact ABS moulded body
- Panel-mount or handheld use
- RYB / RBY phase rotation check




PSI-2 · PHASE SEQUENCE INDICATOR

## 02 WHAT'S IN THE BOX

✓ Test leads

## 03 TECHNICAL SPECIFICATIONS

| PARAMETER | SPECIFICATION |
|---|---|
| **ELECTRICAL** | |
| Operating Voltage (Horizontal) | 50–500 V AC |
| Operating Voltage (Vertical) | 100–500 V AC |
| Frequency | 25–60 Hz |
| Rating | 30 seconds at 500 V |
| Burden | 15 VA at 500 V |
| **GENERAL** | |
| Body | ABS moulded |
| Dimensions | 96 × 96 × 45 mm |
| Important | Not to be left in the circuit |
| Accessories | Test leads (supplied) |
| Warranty | 12 months against manufacturing defects only |



All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - PSI-2 Product Catalogue.