Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

DIGITAL CLAMP MULTIMETER · TRUE-RMS AC

# DCM 2250 TR

True-RMS AC clamp multimeter · Low-Z ACV · NCV · CAT III 600 V

## 01 KEY FEATURES

- True-RMS AC current
- Low-Z ACV
- NCV and live-wire test
- Data hold and MIN/MAX
- Auto-ranging 6000-count LCD

AC current only - for AC/DC current measurement, see **DCM 5410 TR**.




DCM 2250 TR · DIGITAL CLAMP MULTIMETER

## 02 WHAT'S IN THE BOX

✓ Test leads ✓ Carrying pouch ✓ User manual ✓ 2×AAA batteries

## 03 TECHNICAL SPECIFICATIONS

| PARAMETER | SPECIFICATION |
|---|---|
| **CURRENT** | |
| AC Current Ranges | 6 A / 60 A / 600 A / 1000 A (True-RMS) |
| DC Current | Not available - AC current only |
| Jaw Opening (Max.) | 40 mm |
| **VOLTAGE & RESISTANCE** | |
| DC Voltage | 600 mV / 6 V / 60 V / 600 V / 1000 V |
| AC Voltage (True-RMS) | 6 V / 60 V / 600 V / 750 V |
| Low Impedance ACV | 6 V / 60 V / 300 V - ≤3 KΩ input |
| Resistance | 600Ω / 6KΩ / 60KΩ / 600KΩ / 6MΩ / 20MΩ / 60MΩ |
| **DISPLAY & SAFETY** | |
| Display | 6000 Counts LCD, auto-ranging |
| NCV / Live Wire Test | Provided |
| Safety Category | CAT III 600 V |
| **GENERAL** | |
| Power Supply | 2×AAA Batteries |
| Dimensions (L×W×H) | 230 × 75 × 40 mm |
| Weight (incl. battery) | Approx. 315 g |
| Warranty | 12 months against manufacturing defects only |



ISO 9001:2015 CERTIFIED

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - DCM 2250 TR Product Catalogue.