Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

RELAY TEST SET · THREE PHASE

# RTS-33

3-phase relay test set · full 0–360° phase control · two-unit system

## 01 KEY FEATURES

- Full 0–360° phase angle control
- Two-unit system with phase shifter
- Phase-to-phase fault mode
- Digital timer, two ranges
- Built-in phase sequence check

## 02 WHAT'S IN THE BOX

- ✓ Operation manual
- ✓ Schematic circuit diagram
- ✓ Works test report
- ✓ 1m interconnection cable (Unit 1 to Unit 2)
- ✓ 4-core, 5m mains input cable



RTS-33 · RELAY TEST SET

## 03 TECHNICAL SPECIFICATIONS

| PARAMETER | SPECIFICATION |
|---|---|
| **INPUT & OUTPUT** | |
| Input | 415 V ±10%, 3 phase, 4 wire, 50 Hz A.C. |
| Burden | 250 VA (current and voltage circuits) |
| Test Current Taps | 0–1/5/10/25/50A (0–100% regulation per tap) |
| Duty | Continuous up to 10A; 25A & 50A: intermittent (5 min ON, 10 min OFF) |
| Test Voltage | 0–110% of 110V ph-ph (63.5V ph-N), 3-phase, continuously variable |
| Fixed DC Voltage | Isolated 30V / 110V / 220V at 100 VA, available for 30 min |
| **PHASE & TIMING** | |
| Phase Angle | 0–360° - coarse 60° steps + fine ±30° (Unit 2, static phase-shifter) |
| Phase Angle Meter | 360° range, 1° resolution |
| Time Measurement | 0–9.999 sec (0.001s res.) and 0–99.99 sec (0.01s res.) |
| **METERING** | |
| Current Metering | CT-operated ammeter per phase, 0–1A, 0–100% scaled, ±1% accuracy |
| Voltage Metering | 0–200V, ±1% accuracy, 0.1V resolution, phase selector |
| **GENERAL** | |
| Construction | Two-unit system; 1m interconnection cable; 4-core 5m mains cable |
| Warranty | 12 months against manufacturing defects only |



All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - RTS-33 Product Catalogue.