



Cambridge Instruments
& Engg. Co.

EST. 1963 · HOWRAH, INDIA

HV TEST SET · A.C. BREAKDOWN / WITHSTAND

CIE/5050A

Robust powder-coated AC HV breakdown/withstand test set - 0-3 kV or 0-5 kV, 25/50 mA selectable. Analog moving-iron metering, memory device.

3kV or 5kV

TWO OUTPUT VARIANTS, SPECIFY AT ORDER

25/50mA

TOGGLE-SELECTABLE TRIPPING CURRENT

Memory Device

RETAINS BREAKDOWN READING

AC High Voltage Test Set

An A.C. high-voltage breakdown/withstand test set for fast, accurate testing of electrical and electronic materials, components, equipment, and panel boards - housed in a robust powder-coated M.S. cabinet, with a cast-resin H.V. transformer built to withstand frequent sparkover and momentary short-circuit conditions.

- **0-3kV or 0-5kV output** - continuously variable
- **25/50mA tripping current** - toggle-switch selectable, standard
- **Memory device** - retains breakdown reading after HV trips off
- **Zero-start interlocking** - HV circuit can't energise off-zero
- **Analog moving-iron metering** - kV meter + milliammeter, IS 1248:1983
- **Cast-resin HV transformer** - withstands frequent sparkover



CIE/5050A · HV TEST SET

Manufactured in India since 1963 - trusted by various State Electricity Boards, Indian Railways, cement and metal industries, and other sectors.

01 Full Specification Sheet

PARAMETER	SPECIFICATION
Input	230 V $\pm$ 10%, 50 Hz, 1 phase A.C.
Capacity	50 mA maximum on H.V. side
Tripping Current	25 mA & 50 mA - toggle switch selectable (standard)
Duty Cycle	Intermittent - 5 min ON, 10 min OFF
Mode of Operation	Manual
Metering	Analog moving-iron - kV meter & milliammeter, per IS 1248:1983 (not digital)
Memory Device	Push-button switch retains breakdown reading after H.V. trip
Warranty	12 months against manufacturing defects

Any tripping current setting apart from the standard 25mA/50mA above can be built to order.

02 Available Variants

VARIANT	OUTPUT RANGE	TRIPPING CURRENT
CIE/5050A (3 kV)	0-3 kV A.C.	25 mA & 50 mA, toggle selectable
CIE/5050A (5 kV)	0-5 kV A.C.	25 mA & 50 mA, toggle selectable

03 Typical Applications

- Breakdown/withstand testing of electrical and electronic components and materials
- Equipment and panel board dielectric strength testing
- HV withstand testing in production and site environments

04 What's in the Box

- ✓ One pair of H.V. probe with cable

05 Optional Accessories

- + Alternate tripping current set point