



Cambridge Instruments
& Engg. Co.

EST. 1963 · HOWRAH, INDIA

DIGITAL CLAMP MULTIMETER · TRUE-RMS AC

DCM 2250 TR

True-RMS AC clamp multimeter up to 1000 A, with NCV and Low-Z ACV - AC current only, no DC current.

Up to 1000A

MAX AC CURRENT, TRUE-RMS

CAT III 600V

SAFETY RATING

Low-Z ACV

NO GHOST-VOLTAGE READINGS

Digital Clamp Multimeter - True-RMS AC, up to 1000 A

A True-RMS AC clamp multimeter measuring current up to 1000 A across four ranges, with AC/DC voltage, Low-Z ACV, resistance, and non-contact voltage detection - AC current only, no DC current measurement.

- **AC current up to 1000A** - 6/60/600/1000A, True-RMS
- **Data Hold & MIN/MAX** - capture readings in the field
- **Low-Z ACV** - avoids false ghost-voltage readings
- **NCV & live-wire test** built-in
- **6000-count display**, auto-ranging LCD
- **40mm jaw opening**, CAT III 600V safety
- Powered by **2×AAA batteries**

AC current only - for AC/DC current measurement, see **DCM 5410 TR**.

Manufactured in India since 1963 - trusted by various State Electricity Boards, Indian Railways, cement and metal industries, and other sectors.



DCM 2250 TR · DIGITAL CLAMP MULTIMETER

01 Full Specification Sheet

PARAMETER	SPECIFICATION
AC Current Ranges	6 A / 60 A / 600 A / 1000 A (True-RMS)
DC Current	Not available - AC current only
DC Voltage	600 mV / 6 V / 60 V / 600 V / 1000 V
AC Voltage (True-RMS)	6 V / 60 V / 600 V / 750 V
Low Impedance ACV	6 V / 60 V / 300 V - $\leq 3 \text{ K}\Omega$ input
Resistance	600 Ω / 6K Ω / 60K Ω / 600K Ω / 6M Ω / 20M Ω / 60M Ω
Display	6000 Counts LCD, auto-ranging
NCV / Live Wire Test	Provided
Jaw Opening (Max.)	40 mm
Safety Category	CAT III 600 V
Power Supply	2×AAA Batteries
Dimensions (L×W×H)	230 × 75 × 40 mm
Weight (incl. battery)	Approx. 315 g
Warranty	12 months against manufacturing defects

02 Typical Applications

- AC current measurement on panels and distribution boards
- Electrical maintenance and switchgear testing
- Cable and circuit continuity and live-wire checks

03 What's in the Box

- ✓ Test leads
- ✓ Carrying pouch
- ✓ User manual
- ✓ 2×AAA batteries

Cambridge Instruments & Engg. Co.

cieinstruments.in

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - DCM 2250 TR Product Catalogue.