Cambridge Instruments
& Engg. Co.

EST. 1963 · HOWRAH, INDIA

INSULATION TESTER · MOTOR-CUM-HAND OPERATED

CIE/777 HM

Motor + hand-crank · single-range units, 500 V to 10,000 V

Motor + Hand
WORKS WITH OR WITHOUT MAINS

PI & DAR
SUSTAINED VOLTAGE TESTING

500–10000V
AVAILABLE RANGES, SPECIFY AT ORDER

01 KEY SPECIFICATIONS

DRIVE	Mains motor + hand-crank backup
PI / DAR	Sustained test voltage (motor mode)
ACCURACY	IS: 2992-1987
RESPONSE TIME	3 seconds
SCALE LENGTH	100 mm (approx.)
TERMINALS	Guard & infinity adjuster



CIE/777 HM · INSULATION TESTER

02 TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
DRIVE & MEASUREMENT	
Drive	Mains motor (230V, 50Hz A.C.) + collapsible hand-crank
Scale Length	100 mm (approx.)
Accuracy	As per IS: 2992-1987
Response Time	3 seconds
Range Configuration	Multiple range options available - specify at order
Guard Terminal & Infinity Adjuster	Guard ring & guard terminal eliminate surface-leakage errors; infinity adjuster provided
TEST & SAFETY	
High Voltage Test	Min. 2kV or (rated V + 1)kV A.C. r.m.s., 1 min
Insulation Resistance Test	Better than 50 MΩ at 500V D.C.
GENERAL	
Body	Seasoned wooden cabinet, sunmica finish, detachable lid, handle, lock
Dimensions (top cover)	14 × 10 × 10 inch (approx.)
Weight (top cover)	12 kg (approx.) - vs 9 kg for plain CIE/777
Warranty	12 months against manufacturing defects

Custom ranges and configurations can also be built against specific requirements.

03 APPLICATIONS

- Field testing where mains supply is uncertain
- Sustained PI & DAR testing (motor-driven mode)
- Remote substation and railway traction commissioning
- HV transformer and cable insulation assessment

04 WHAT'S IN THE BOX

✓ Mains cord, 2 metres
✓ 1 pair of H.V. testing leads

05 OPTIONAL ACCESSORIES

+ Rexine carrying case
+ 15-minute timer facility
+ Additional/special H.V. leads, 2m
+ Dual voltage & range option
+ Single voltage, dual range option

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - CIE/777 HM Product Catalogue.