Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

DIGITAL CLAMP MULTIMETER · TRUE-RMS AC

DCM 2250 TR

True-RMS AC current to 1000 A · CAT III 600 V · NCV · Low-Z ACV

Up to 1000A
MAX AC CURRENT, TRUE-RMS

CAT III 600V
SAFETY RATING

Low-Z ACV
NO GHOST-VOLTAGE READINGS

01 KEY SPECIFICATIONS

AC CURRENT	6 / 60 / 600 / 1000 A, True-RMS
VOLTAGE	DC to 1000 V · AC to 750 V
LOW-Z ACV	6 / 60 / 300 V
DISPLAY	6000 counts, auto-ranging
JAW OPENING	40 mm
SAFETY	CAT III 600 V

AC current only - for AC/DC current measurement, see **DCM 5410 TR**.



DCM 2250 TR · DIGITAL CLAMP MULTIMETER

02 TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
CURRENT	
AC Current Ranges	6 A / 60 A / 600 A / 1000 A (True-RMS)
DC Current	Not available - AC current only
Jaw Opening (Max.)	40 mm
VOLTAGE & RESISTANCE	
DC Voltage	600 mV / 6 V / 60 V / 600 V / 1000 V
AC Voltage (True-RMS)	6 V / 60 V / 600 V / 750 V
Low Impedance ACV	6 V / 60 V / 300 V - ≤3 KΩ input
Resistance	600Ω / 6KΩ / 60KΩ / 600KΩ / 6MΩ / 20MΩ / 60MΩ
DISPLAY & SAFETY	
Display	6000 Counts LCD, auto-ranging
NCV / Live Wire Test	Provided
Safety Category	CAT III 600 V
GENERAL	
Power Supply	2×AAA Batteries
Dimensions (L×W×H)	230 × 75 × 40 mm
Weight (incl. battery)	Approx. 315 g
Warranty	12 months against manufacturing defects

03 APPLICATIONS

- AC current measurement on panels and distribution boards
- Electrical maintenance and switchgear testing
- Cable and circuit continuity and live-wire checks

04 WHAT'S IN THE BOX

✓ Test leads ✓ Carrying pouch ✓ User manual
✓ 2×AAA batteries

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - DCM 2250 TR Product Catalogue.