Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

DIGITAL INSULATION TESTER

DIT-2500

2500 V · 50 GΩ · True-RMS multimeter · CAT III

Up to 2500V	50 GΩ	CAT III	380 g
MAX TEST VOLTAGE	MAX RESISTANCE	SAFETY RATING	WEIGHT, HANDHELD

01 KEY SPECIFICATIONS

INSULATION TEST	100 / 250 / 500 / 1000 / 2500 V
IR RANGE	0.1 MΩ – 50 GΩ
DAR / PI	Built-in · 15 s / 30 s / 1 min / 10 min timer
MULTIMETER	True-RMS · AC/DC to 1500 V
SAFETY	CAT III 1000 V · IEC 61010
POWER	Li-ion 3.7 V × 2, rechargeable



DIT-2500 · INSULATION TESTER

02 TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
INSULATION RESISTANCE TEST	
Test voltage	100 / 250 / 500 / 1000 / 2500 V
Resistance range	0.1 MΩ – 50 GΩ
Short-circuit current	≥ 1 mA
DAR	1 min : 15 s and 1 min : 30 s
PI	10 min : 60 s
MULTIMETER (TRUE-RMS)	
DC / AC voltage	1 mV – 1500 V
Resistance	0.1 Ω – 60 MΩ
Capacitance	0.001 nF – 100 mF
GENERAL	
Safety category	CAT III 1000 V
Battery	Li-ion 3.7 V × 2, rechargeable
Dimensions (L × W × H)	189 × 89 × 55 mm
Weight	Approx. 380 g
Warranty	12 months

03 APPLICATIONS

- Insulation resistance: motors, transformers, cables
- DAR / PI insulation quality assessment
- Switchgear, panel and cable commissioning

04 WHAT'S IN THE BOX

✓ Test leads ✓ Charging set ✓ Instruction manual

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - DIT-2500 Product Catalogue.