Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

DIGITAL INSULATION TESTER · AUTO-RANGE

DIT-5000

Up to 5000 V · 200 GΩ · auto-ranging · HV live-output indicator

Up to 5000V
MAX OUTPUT VOLTAGE

200 GΩ
MAX INSULATION RESISTANCE

Auto-Range
AUTO ZERO + POLARITY

01 KEY SPECIFICATIONS

TEST VOLTAGE	500 / 1000 / 2500 / 5000 V
IR RANGE	1 MΩ – 200 GΩ
SHORT-CIRCUIT CURRENT	1 mA
DISPLAY	3½-digit LCD, 35 mm digits
AC VOLTAGE	Up to 750 V (secondary)
POWER	6 × 1.5 V AA



DIT-5000 · DIGITAL INSULATION TESTER

02 TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
INSULATION RESISTANCE TEST	
Output Voltage	500 V / 1000 V / 2500 V / 5000 V
Insulation Resistance	1 MΩ – 200 GΩ
Short Circuit Current	1 mA
Acc. 1M–200MΩ	±(3% × reading + 5 digits)
Acc. 200M–10GΩ	±(5% × reading + 5 digits)
Acc. 10G–200GΩ	±(10% × reading + 5 digits)
DISPLAY & MEASUREMENT	
AC Voltage Measurement	Up to 750 V (secondary function)
Display	3½-digit LCD, 68×55 mm, 35 mm characters, backlit
Ranging	Auto-range, auto zero calibration, auto polarity
HV Indicator	High-voltage LED - lights when output is live
GENERAL	
Power Supply	6×1.5 V AA batteries (replaceable)
Dimensions (L×W×H)	218 × 122 × 75 mm
Weight	Approx. 900 g
Warranty	12 months against manufacturing defects

03 APPLICATIONS

- Motor and rotating-machinery insulation testing at higher voltages
- HV transformer and cable insulation testing up to 5000 V
- Utilities and large industrial plants requiring 5000V class testing

04 WHAT'S IN THE BOX

- ✓ Test leads
- ✓ 6×AA batteries
- ✓ User manual
- ✓ Carrying box

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - DIT-5000 Product Catalogue.