Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

MICRO-OHM METER · BENCH-TOP, 4-TERMINAL KELVIN

MR-253A

4-terminal Kelvin · 1999 µΩ to 19.99 kΩ · 8 ranges · ±0.5%

4-Terminal
KELVIN MEASUREMENT

µΩ to kΩ
8 RANGES, SINGLE UNIT

±0.5% ±2 digits
ACCURACY

01 KEY SPECIFICATIONS

TECHNIQUE	4-terminal (Kelvin)
RANGES	8 ranges, 1999 µΩ to 19.99 kΩ
ACCURACY	±0.5% ±2 digits
TEST CURRENT	1 A down to 0.01 mA, by range
DISPLAY	3½-digit LED, 1999 counts
POWER	230 V, 50 Hz



MR-253A · MICRO-OHM METER

02 TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
Display	3½-digit, 1999 counts, seven-segment LED
Measurement Technique	4-terminal (Kelvin) - eliminates lead & contact resistance error
Accuracy	±0.5% ±2 digits
Power	230 V, 50 Hz, single phase
Dimensions (W×H×D)	192 × 96 × 230 mm (approx.)
Weight	2.25 kg (approx.)
Warranty	12 months against manufacturing defects

03 MEASUREMENT RANGES - RESOLUTION & TEST CURRENT

RANGE	RESOLUTION	TEST CURRENT
0–1999 µΩ	1 µΩ	1 A
0–19.99 mΩ	0.01 mΩ	1 A
0–199.9 mΩ	0.1 mΩ	1 A
0–1999 mΩ	1 mΩ	0.1 A (100 mA)
0–19.99 Ω	0.01 Ω	0.01 A (10 mA)
0–199.9 Ω	0.1 Ω	0.001 A (1 mA)
0–1999 Ω	1 Ω	0.0001 A (0.1 mA)
0–19.99 kΩ	0.01 kΩ	0.00001 A (0.01 mA)

04 APPLICATIONS

- Cable and wire resistance measurement
- Transformer and motor winding resistance checks
- Switch and relay contact resistance testing
- PCB track resistance testing and ammeter shunt calibration

05 WHAT'S IN THE BOX

✓ 2 pairs of test leads

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - MR-253A Product Catalogue.