Cambridge Instruments
& Engg. Co.

EST. 1963 · HOWRAH, INDIA

PHASE SEQUENCE INDICATOR · DISC ROTATING TYPE

PSI-1

Disc-rotation indication · 100–500 V AC · 25–65 Hz

Disc Rotation
VISUAL RYB/RBY INDICATION

100–500V AC
25–65HZ OPERATING RANGE

Horizontal Use
PER MANUFACTURER SPEC

01 KEY SPECIFICATIONS

INDICATION	Disc rotation, RYB / RBY
VOLTAGE	100–500 V AC
FREQUENCY	25–65 Hz
CONNECTION	3-lead R / Y / B, crocodile clips
POSITION	Horizontal only
BODY	Bakelite



PSI-1 · PHASE SEQUENCE INDICATOR

02 TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
Indication Method	Disc rotation
Body	Bakelite
Operating Voltage	100–500 V AC
Frequency	25–65 Hz
Operating Position	Horizontal only
Accessories	3 Nos. 1m testing leads (R/Y/B) with crocodile clips, and carrying case
Warranty	12 months against manufacturing defects

03 APPLICATIONS

- 3-phase supply phase sequence verification
- Motor connection commissioning
- Panel and switchboard testing

04 WHAT'S IN THE BOX

- ✓ 3 Nos. 1m testing leads (R/Y/B)
- ✓ Carrying case

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - PSI-1 Product Catalogue.