Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

PHASE SEQUENCE INDICATOR · ABS MOULDED

PSI-2

96 × 96 mm · 50–500 V AC · 25–60 Hz · ABS body

50–500V AC
POSITION-DEPENDENT RANGE

25–60Hz
OPERATING FREQUENCY

Not for Circuit Use
NOT TO BE LEFT IN CIRCUIT

01 KEY SPECIFICATIONS

VOLTAGE	50–500 V AC (by orientation)
FREQUENCY	25–60 Hz
RATING	30 seconds at 500 V
BURDEN	15 VA at 500 V
SIZE	96 × 96 × 45 mm
BODY	ABS moulded



PSI-2 · PHASE SEQUENCE INDICATOR

02 TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
ELECTRICAL	
Operating Voltage (Horizontal)	50–500 V AC
Operating Voltage (Vertical)	100–500 V AC
Frequency	25–60 Hz
Rating	30 seconds at 500 V
Burden	15 VA at 500 V
GENERAL	
Body	ABS moulded
Dimensions	96 × 96 × 45 mm
Important	Not to be left in the circuit
Accessories	Carrying case and test leads (supplied)
Warranty	12 months against manufacturing defects

03 APPLICATIONS

- 3-phase phase sequence check
- Switchboard commissioning
- Motor connection verification

04 WHAT'S IN THE BOX

✓ Carrying case ✓ Test leads

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - PSI-2 Product Catalogue.