Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

INSULATION TESTER · MOTOR OPERATED

# CIE/777 Range Guide

Mains-motor driven, wooden cabinet

## Every standard voltage and range

230 V mains motor, rated voltages 500, 1,000, 2,500, 5,000 and 10,000 V. Pick the rated test voltage first, then the insulation resistance range that suits your equipment. Each combination below is a standard build.

| 5 | 14 | 500–10,000 |
|---|---|---|
| RATED VOLTAGES | STANDARD RANGES | VOLTS |



CIE/777 · ILLUSTRATIVE IMAGE

## 01 STANDARD RANGES BY RATED VOLTAGE

| RATED VOLTAGE | INSULATION RESISTANCE RANGE (MΩ) |
|---|---|
| 500 V | 0–1,000 |
| 1,000 V | 0–2,000 |
| 2,500 V | 0–5,000 · 0–10,000 · 0–20,000 |
| 5,000 V | 0–5,000 · 0–10,000 · 0–20,000 · 50–50,000 · 100–100,000 |
| 10,000 V | 0–10,000 · 0–20,000 · 50–50,000 · 100–100,000 |

*Ranges shown are the standard builds. Any other range can be manufactured against specific requirements.*

## 02 COMBINING VOLTAGES AND RANGES

### Dual voltage & dual insulation range

Two rated voltages, each with its own range. The selected range must lie within the rated resistance listed for that voltage. Not available for 10,000 V.

### Single voltage, dual insulation range

One rated voltage with two insulation ranges within the listed rated resistance for that voltage. Not available for 10,000 V.

### Dual voltage, single insulation range

Two rated voltages sharing one insulation range within the listed rated resistance. Not available for 10,000 V.



All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - CIE/777 Range Guide.

INSULATION TESTER · MOTOR OPERATED

# CIE/777 Range Guide

Multi-range options, specifications, accessories and ordering

## 03 MULTIRANGE SERIES: CIE/777/MR

| SERIES | RATED VOLTAGE | INNER SCALE (MΩ) | OUTER SCALE (MΩ) |
|---|---|---|---|
| **MR-A** | 5,000 V<br>2,500 V<br>1,000 V | 0–5,000<br>0–2,500<br>0–1,000 | 50–100,000<br>25–50,000<br>10–20,000 |
| **MR-B** | 5,000 V<br>2,500 V<br>1,000 V | 0–2,000<br>0–1,000<br>0–500 | 10–10,000<br>5–5,000<br>2–2,000 |
| **MR-C** | 5,000 V<br>2,500 V | 100–100,000<br>50–50,000 | Single scale<br>Single scale |
| **MR-D** | 5,000 V<br>2,500 V | 0–5,000<br>0–2,500 | 50–100,000<br>25–50,000 |
| **MR-E** | 5,000 V<br>2,500 V<br>1,000 V | 50–50,000<br>25–25,000<br>10–10,000 | Single scale<br>Single scale<br>Single scale |

*Multirange instruments carry a range selector switch, so one instrument covers every voltage and range listed in its series. Any other configuration can be built to order.*

## 04 KEY SPECIFICATIONS

| | |
|---|---|
| Drive | **Mains motor, 230 V, 50 Hz A.C.** |
| Body | **Seasoned wooden cabinet with sunmica finish, detachable lid, handle, lock** |
| Scale Length | **100 mm (approx.)** |
| Accuracy | **As per IS: 2992-1987** |
| Dimensions (incl. top cover, approx.) | **14 × 10 × 10 inch** |
| Weight (incl. top cover) | **9 kg (approx.)** |
| Response Time | **3 seconds** |

## 05 SUPPLIED AND OPTIONAL

**Supplied as standard**

- ✓ Mains cord, 2 m
- ✓ 1 pair of H.V. testing leads

**Optional, at extra cost**

- Carrying case
- 15-minute timer facility
- Testing leads, 1 m or 2 m
- Additional / special-grade H.V. testing leads, 2 m

## 06 HOW TO ORDER

To order, quote the **model**, the **rated voltage** and the **insulation range**, for example **`CIE/777, 500 V / 0–1,000 MΩ`**. Any range not listed can be manufactured against specific requirements - enquire.

**cieinstruments@gmail.com · +91 98300 91260 · +91 98300 92117**



All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - CIE/777 Range Guide.