Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

DIGITAL CLAMP MULTIMETER · TRUE-RMS AC/DC

DCM 5410 TR

True-RMS AC/DC clamp multimeter · capacitance · frequency · temperature

01 KEY FEATURES

- True-RMS AC and DC current
- Low-Z ACV
- NCV and live-wire test
- Capacitance, frequency and temperature
- Auto-ranging 6000-count LCD
- Inrush current and low-pass filter ACV



DCM 5410 TR · DIGITAL CLAMP MULTIMETER

02 TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
CURRENT	
AC Current Ranges	60 A / 600 A / 1000 A (True-RMS)
DC Current Ranges	60 A / 600 A / 1000 A
Current Accuracy	±(4.0% + 10) AC and DC; AC response 50 Hz – 60 Hz
Jaw Opening (Max.)	40 mm
VOLTAGE & RESISTANCE	
DC Voltage	600 mV / 6 V / 60 V / 600 V / 1000 V
AC Voltage (True-RMS)	6 V / 60 V / 600 V / 750 V
Low Impedance ACV	6 V / 60 V / 300 V - ≤3 KΩ input
Voltage Accuracy	DC ±(0.5% + 7) to 60 V, ±(1.0% + 10) above AC ±(1.0% + 10) to 60 V, ±(1.0% + 12) above
Low-Pass Filter ACV (V.F.C)	40 Hz – 200 Hz, ±(5.0% + 10), for VFD outputs
Resistance	600Ω / 6KΩ / 60KΩ / 600KΩ / 6MΩ / 20MΩ / 60MΩ
OTHER MEASUREMENTS	
Capacitance	1 nF – 10 mF (8 ranges)
Frequency	10 Hz – 10 MHz, ±(0.3% + 3); duty cycle 10% – 90%
Temperature	–20°C to 1000°C / –4°F to 1832°F (supplied probe: –20°C to 250°C)
DISPLAY & SAFETY	
Display	6000 Counts LCD, auto-ranging
NCV / Live Wire Test	Provided
Safety Category	CAT III 600 V
GENERAL	
Power Supply	2×AAA 1.5V Batteries
Dimensions (L×W×H)	230 × 75 × 40 mm
Weight (incl. battery)	Approx. 313 g
Warranty	12 months against manufacturing defects only

03 APPLICATIONS

- AC and DC current measurement on panels and boards
- Solar and battery system diagnostics (DC clamp)
- Electrical maintenance and switchgear testing
- Combined electrical and temperature diagnostics

04 WHAT'S IN THE BOX

- ✓ Test leads
- ✓ K-type temperature probe
- ✓ Carrying pouch
- ✓ User manual
- ✓ 2×AAA batteries

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - DCM 5410 TR Product Catalogue.