Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

DIGITAL INSULATION TESTER · COMPACT, RECHARGEABLE

# DIT-5005

3½-digit LCD · rechargeable Ni-Cd · IS 10656-1983

## 01 KEY FEATURES

- 3½-digit LCD, direct readout
- Rechargeable Ni-Cd cells
- Bench-top or hand-held use
- Lo-Bat indication
- Rugged ABS body




DIT-5005 · DIGITAL INSULATION TESTER

## 02 WHAT'S IN THE BOX

✓ Carrying case ✓ Charging cord ✓ Testing lead, 1m ✓ Instruction manual

## 03 TECHNICAL SPECIFICATIONS

| PARAMETER | SPECIFICATION |
|---|---|
| **MEASUREMENT** | |
| Display | 3½ digits, L.C.D. |
| Accuracy - Insulation | ±3% of F.S. ±5 digits |
| Accuracy - Output Voltage (DC) | ±10% at rated resistance |
| Confirms To | IS 10656-1983 |
| Range Configuration | 4 standard ranges - see table below |
| **TEST & SAFETY** | |
| H.V. Test | 2 kV A.C. (r.m.s.), 1 min., circuit to containing case |
| Insulation Resistance Test | More than 50 MΩ at 500V D.C. |
| **GENERAL** | |
| Dimensions (L×W×H) | 172 × 98 × 38 mm (approx.) |
| Weight | 550 g (approx.) |
| Warranty | 12 months against manufacturing defects only |

## 04 AVAILABLE RANGES

| RATED VOLTAGE | RATED RESISTANCE RANGE |
|---|---|
| 500 V DC | 0–200 MΩ |
| 500 V DC | 0–1000 MΩ |
| 1000 V DC | 0–200 MΩ |
| 1000 V DC | 0–2000 MΩ |

*Any other range can be manufactured against specific requirements.*



ISO 9001:2015 CERTIFIED

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - DIT-5005 Product Catalogue.