Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

MICRO-OHM METER · BENCH-TOP, 4-TERMINAL KELVIN

# MR-253A

Digital micro-ohm meter · 4-terminal Kelvin · 3½-digit LED display

## 01 KEY FEATURES

- 4-terminal Kelvin technique
- 3½-digit seven-segment LED display
- Automatic test-current scaling by range
- MOS LSI technology




MR-253A · MICRO-OHM METER

## 02 TECHNICAL SPECIFICATIONS

| PARAMETER | SPECIFICATION |
|---|---|
| Display | 3½-digit, 1999 counts, seven-segment LED |
| Measurement Technique | 4-terminal (Kelvin) - eliminates lead & contact resistance error |
| Accuracy | ±0.5% ±2 digits |
| Power | 230 V, 50 Hz, single phase |
| Dimensions | 285 × 210 × 100 mm (approx.) |
| Weight | 2.8 kg (approx.) |
| Warranty | 12 months against manufacturing defects only |

## 03 MEASUREMENT RANGES - RESOLUTION & TEST CURRENT

| RANGE | RESOLUTION | TEST CURRENT |
|---|---|---|
| 0–1999 µΩ | 1 µΩ | 2 A |
| 0–19.99 mΩ | 0.01 mΩ | 1 A |
| 0–199.9 mΩ | 0.1 mΩ | 1 A |
| 0–1999 mΩ | 1 mΩ | 0.1 A (100 mA) |
| 0–19.99 Ω | 0.01 Ω | 0.01 A (10 mA) |
| 0–199.9 Ω | 0.1 Ω | 0.001 A (1 mA) |
| 0–1999 Ω | 1 Ω | 0.0001 A (0.1 mA) |
| 0–19.99 kΩ | 0.01 kΩ | 0.00001 A (0.01 mA) |

## 04 APPLICATIONS

- Cable and wire resistance measurement
- Transformer and motor winding resistance checks
- Switch and relay contact resistance testing
- PCB track resistance testing and ammeter shunt calibration

## 05 WHAT'S IN THE BOX

✓ 2 pairs of test leads



All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - MR-253A Product Catalogue.