Systems TECH

# HTM-590 CONTACT TYPE DIGITAL TACHOMETER

## MODEL NUMBER - HTM 590




## KEY FEATURES TRUSTED FOR QUALITY AND RELIABILITY

- Full Digital, Micro Controller LSI circuit design for high reliability and versatility.
- Comes with a sturdy, easy to carry/handle carrying case box with foam padding for protection against impact.
- Ergonomically designed for handheld based operations for risk free RPM measurement at all times.
- Excellent Quality, compact size and accurate reading.
- Economic and effective Battery power utilisation.

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Ranges:** | 60 RPM – 50,000 RPM<br>6m/min – 5000 m/min (Surface speed) |
| **Resolution:** | 0.1 upto 1000 RPM/1 above 1000 RPM<br>0.01 upto 100 meter/min/0.1 above 100 meter/min |
| **Display Type:** | 5 digits, 10mm(0.38") height RED LED |
| **Accuracy:** | +/- 0.05 + 1 Digit |
| **Sampling Rate:** | 1 second |
| **Time Base:** | Quartz Crystal Controlled |
| **Low Battery:** | Indicated by "Lobat" when the battery voltage drops below operating voltage |
| **Memory Recall:** | 'Last', 'Max', 'Min' Values memorized automatically, upto 120sec can be recalled |
| **Power Source:** | 4 X 1.5V AA Battery. Auto Shut off feature included |
| **Battery Life:** | 90hrs for alkaline batteries \| 30hrs for Carbon-Zinc batteries |
| **Operating Temp:** | 0° Celsius to 60° Celsius (32° F to 140° F ) |
| **Size:** | 70 x 200 x 40mm (2.8 x 7.8 x 1.6 inch) |
| **Weight:** | 320 grams |

| **Standard Accessories:** | | |
|---|---|---|
| | Male rubber contact tip | 2 |
| | Female rubber contact tip | 2 |
| | Peripheral rubber contact tip reflective tape (Marks) | 1 |
| | Padded Carrying Case | 1 |
| | User manual | 1 |