TS-200 TEMPERATURE SENSOR

MODEL NUMBER - TS-200



KEY FEATURES

- Truly wireless –WiFi enabled (LoRaWAN version also available)
- Comes with a double sided sticker to easily mount it on the outer side of your refrigeration unit.
- Alarm temperature max, min (30, -20)
- Real-time, instant updates Readily available APIs for integration under 30 minutes!
- Temperature measurement range -50°C to 125°C Maximum resolution +/- 0.25°C
- Power Supply external microUSB. 5V, 500mA.

TECHNICAL SPECIFICATIONS

Sensor Ranges:	NDP –40°C to 125°C | DP: –55°C to +125°C
Accuracy:	NDP: ±0.5°C from –25°C to 85°C DP: ±0.5°C from -10°C to +85°C
Resolution:	0.0625°C
Power requirements:	5V DC micro USB max 30mA current draw (USB version)/ max 500mA current draw 2200mAh rechargeable battery (for Li-Ion version only) 2x AA Alkaline 1.5V cells (for non-rechargeable versions only)
Sensor cable:	50 cm, 1mm height, Flat Ribbon Cable
Processor:	32-bit processor running at 80Mhz and with a complete 2.4Ghz WiFi stack
Configurable parameters:	Measurement interval 60s Temperature delta to trigger data transmission +/- 1°C Alarm temperature max, min (30, -20)
Alarm:	Audio 70dB (min.) sweep tone Flashing screen with Alarm icon
Input:	Capacitive, non-mechanical touch sense x 1 (USB version only) Serial over USB commands (USB version only)