Cambridge Instruments
& Engg. Co.

EST. 1963 · HOWRAH, INDIA

INSULATION TESTER · MULTIRANGE, METAL BODY

CIE/444/MR

Series MR-2 · 1000 / 500 / 250 V

Multirange insulation tester · selectable voltage · built-in continuity range

01 KEY FEATURES

- Selectable multi-voltage operation
- Built-in continuity range
- Hand-driven, no battery
- Anti-magnetic aluminium, die-cast body

MR-5 to MR-8 are wooden-body only (see **CIE/666/MR**) - not available in this metal-body configuration.



CIE/444/MR · INSULATION TESTER · REPRESENTATIVE IMAGE

02 TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
Body	Anti-magnetic aluminium
Generator Type	Hand-driven
Series	MR-2
Continuity Range	Built-in as standard on all MR series
Warranty	12 months against manufacturing defects only

Any other configuration can be built to order - enquire.

03 SERIES SPECIFICATION - VOLTAGE, RANGE & CONTINUITY

SERIES	VOLTAGE & RESISTANCE RANGES	CONTINUITY RANGE
MR-2	1000V/0–200MΩ · 500V/0–100MΩ · 250V/0–50MΩ	0–1 KΩ

04 APPLICATIONS

- Multi-voltage insulation testing on a single instrument
- Utilities needing flexible voltage selection
- Cable and transformer testing at varying voltages
- Substation and EPC commissioning

05 OPTIONAL ACCESSORIES

+ Carrying case
+ Test leads, 1m
+ H.V. test leads, 2m (general)
+ H.V. test leads, 2m (special)

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - CIE/444/MR MR-2 Product Catalogue.