



**Cambridge Instruments
& Engg. Co.**

EST. 1963 · HOWRAH, INDIA

INSULATION TESTER · MULTIRANGE, METAL BODY

CIE/444/MR

Selectable multi-voltage insulation tester in metal body, with built-in continuity range as standard - Series MR-1 to MR-4.

MR-1 TO MR-4

Multirange Insulation Tester - Metal Body

A multirange version of the hand-driven CIE/444, with a selector switch providing multiple rated test voltages on one instrument, plus a continuity range built in as standard.

- **Selectable multi-voltage** - one instrument, 3 ranges per series
- **Continuity range built-in** - standard on all MR series
- **Hand-driven** - no batteries required
- **Anti-magnetic aluminium body** - die-cast, rugged
- **4 series available** - MR-1 to MR-4, metal body

MR-5 to MR-8 are wooden-body only (see **CIE/666/MR**) - not available in this metal-body configuration.

Manufactured in India since 1963 - trusted by various State Electricity Boards, Indian Railways, cement and metal industries, and other sectors.



- M** MR-1 to MR-4 Series available, metal body
- ✓** Built-In Continuity range, standard
- ⊖** Battery-Free Hand-cranked generator

01 Full Specification Sheet

PARAMETER	SPECIFICATION
Body	Anti-magnetic aluminium
Generator Type	Hand-driven
Series Available (Metal Body)	MR-1 to MR-4 only
Continuity Range	Built-in as standard on all MR series
Warranty	12 months against manufacturing defects

Any configuration apart from the standard MR series above can be built to order.

02 Available Series - Voltage, Range & Continuity

SERIES	VOLTAGE & RESISTANCE RANGES	CONTINUITY RANGE
MR-1	1000V/0-2000MΩ · 500V/0-1000MΩ · 250V/0-500MΩ	0-20 KΩ
MR-2	1000V/0-200MΩ · 500V/0-100MΩ · 250V/0-50MΩ	0-1 KΩ
MR-3	500V/0-1000MΩ · 250V/0-500MΩ · 100V/0-200MΩ	0-5 KΩ
MR-4	500V/0-100MΩ · 250V/0-50MΩ · 100V/0-20MΩ	0-1 KΩ

03 Typical Applications

- Multi-voltage insulation testing on a single instrument
- Utilities needing flexible voltage selection
- Cable and transformer testing at varying voltages
- Substation and EPC commissioning

04 Optional Accessories

- + Carrying case
- + Test leads, 1m
- + H.V. test leads, 2m (general)
- + H.V. test leads, 2m (special)