



Cambridge Instruments
& Engg. Co.

EST. 1963 · HOWRAH, INDIA

INSULATION TESTER · MULTIRANGE, MOTORISED, DUAL-SCALE

CIE/777/MR

Dual-scale motorised insulation tester - inner and outer scale readings cover two ranges per voltage. Series MR-A to MR-E.

MR-A TO MR-E

Multirange Motorised Insulation Tester

A motorised multi-voltage insulation tester with a dual-scale (inner/outer) reading arrangement - the inner scale covers a standard resistance range and the outer scale an extended range, at each rated voltage, so the operator can read either range without switching instruments. Five series (MR-A to MR-E) cover different voltage and range combinations.

- **Motorised drive** - mains, 230V/50Hz A.C.
- **Dual-scale display** - inner & outer ranges, no switching
- **5 series, MR-A to MR-E** - different range combinations
- **5000V maximum** - standard on every series
- **Sustained PI & DAR testing** - full motor-driven capability

Manufactured in India since 1963 - trusted by various State Electricity Boards, Indian Railways, cement and metal industries, and other sectors.



- M** **Motorised** Mains, 230V/50Hz A.C.
- ✓** **Dual-Scale** Inner + outer range, no switch
- V** **5000V Maximum** Standard on all 5 series

01 Full Specification Sheet

PARAMETER	SPECIFICATION
Drive	Motorised (mains, 230 V, 50 Hz A.C.)
Series Available	MR-A to MR-E
Display	Dual-scale inner/outer (MR-A, MR-B, MR-D) or single-scale (MR-C, MR-E)
Physical Specs	Varies by series - contact us to confirm
Warranty	12 months against manufacturing defects

Any configuration apart from the standard MR series above can be built to order.

02 Available Series - Voltage, Inner Scale & Outer Scale

SERIES	VOLT.	INNER	OUTER
MR-A	5000 V	0-5000 MΩ	50-100000 MΩ
MR-A	2500 V	0-2500 MΩ	25-50000 MΩ
MR-A	1000 V	0-1000 MΩ	10-20000 MΩ
MR-B	5000 V	0-2000 MΩ	10-10000 MΩ
MR-B	2500 V	0-1000 MΩ	5-5000 MΩ
MR-B	1000 V	0-500 MΩ	2-2000 MΩ

SERIES	VOLT.	INNER	OUTER
MR-C	5000 V	100-100000 MΩ	-
MR-C	2500 V	50-50000 MΩ	-
MR-D	5000 V	0-5000 MΩ	50-100000 MΩ
MR-D	2500 V	0-2500 MΩ	25-50000 MΩ
MR-E	5000 V	50-50000 MΩ	-
MR-E	2500 V	25-25000 MΩ	-
MR-E	1000 V	10-10000 MΩ	-

03 Typical Applications

- Transformer and HV switchgear insulation testing requiring both standard and extended resistance range
- PI and dielectric absorption testing across multiple voltage classes
- Industrial and utility insulation maintenance programs

04 Optional Accessories

- + Carrying case
- + Test leads, 1m
- + H.V. test leads, 2m (general)
- + H.V. test leads, 2m (special)
- + Timer
- + Any other range - on request