



Cambridge Instruments  
& Engg. Co.

EST. 1963 · HOWRAH, INDIA

INSULATION TESTER · MULTIRANGE, MOTOR-CUM-HAND, DUAL-SCALE

# CIE/777 HM/MR

Dual-scale motor-cum-hand driven insulation tester — inner and outer scale readings cover two ranges per voltage, with hand-crank backup. Series MR-A to MR-E.

MR-A TO MR-E

## Multirange Motor-cum-Hand Driven Insulation Tester

Combines the dual-scale (inner/outer) multirange capability of the CIE/777/MR with the motor-and-hand dual-drive of the CIE/777 HM. The motor-driven mode enables sustained PI and dielectric absorption testing; the hand-crank backup allows operation where mains power is unavailable. All five series (MR-A to MR-E) are available in this configuration.

- **Motor + hand-crank backup** — works with or without mains
- **Dual-scale display** — inner & outer ranges, no switching
- **5 series, MR-A to MR-E** — different range combinations
- **5000V maximum** — standard on every series
- **Sustained PI & DAR testing** — motor-driven mode

Manufactured in India since 1963 — trusted by various State Electricity Boards, Indian Railways, cement and metal industries, and other sectors.



- M Motor + Hand** Works with or without mains
- ✓ Dual-Scale** Inner + outer range, no switch
- V 5000V Maximum** Standard on all 5 series

### 01 Full Specification Sheet

| PARAMETER        | SPECIFICATION                                                          |
|------------------|------------------------------------------------------------------------|
| Drive            | Mains motor (230 V, 50 Hz A.C.) + collapsible hand-crank               |
| Series Available | MR-A to MR-E                                                           |
| Display          | Dual-scale inner/outer (MR-A, MR-B, MR-D) or single-scale (MR-C, MR-E) |
| Physical Specs   | Varies by series — contact us to confirm                               |
| Warranty         | 12 months against manufacturing defects                                |

Any configuration apart from the standard MR series above can be built to order.

### 02 Available Series — Voltage, Inner Scale & Outer Scale

| SERIES | VOLT.  | INNER     | OUTER        |
|--------|--------|-----------|--------------|
| MR-A   | 5000 V | 0–5000 MΩ | 50–100000 MΩ |
| MR-A   | 2500 V | 0–2500 MΩ | 25–50000 MΩ  |
| MR-A   | 1000 V | 0–1000 MΩ | 10–20000 MΩ  |
| MR-B   | 5000 V | 0–2000 MΩ | 10–10000 MΩ  |
| MR-B   | 2500 V | 0–1000 MΩ | 5–5000 MΩ    |
| MR-B   | 1000 V | 0–500 MΩ  | 2–2000 MΩ    |

| SERIES | VOLT.  | INNER         | OUTER        |
|--------|--------|---------------|--------------|
| MR-C   | 5000 V | 100–100000 MΩ | —            |
| MR-C   | 2500 V | 50–50000 MΩ   | —            |
| MR-D   | 5000 V | 0–5000 MΩ     | 50–100000 MΩ |
| MR-D   | 2500 V | 0–2500 MΩ     | 25–50000 MΩ  |
| MR-E   | 5000 V | 50–50000 MΩ   | —            |
| MR-E   | 2500 V | 25–25000 MΩ   | —            |
| MR-E   | 1000 V | 10–10000 MΩ   | —            |

### 03 Typical Applications

- Remote field testing with backup hand drive — dual-scale multirange coverage
- Multi-voltage HV commissioning and PI testing
- EPC contractors and utilities needing both motor and hand-drive flexibility

### 04 Optional Accessories

- + Carrying case
- + Test leads, 1m
- + H.V. test leads, 2m (general)
- + H.V. test leads, 2m (special)
- + Timer
- + Any other range — on request