

Type your text

National University of Computer and Emerging Sciences

Lab Manual

Computer Organization and Assembly Language



Lab 05

Instructor	Raja Muzammil
Class	CS3
Sections	3B
Semester	Fall 2022

Fast School of Computing

FAST-NU, Lahore, Pakistan

Objectives

- Use of subroutines in assembly
- Subroutines Saving and restoring registers
- Subroutines passing parameters through stack

Contents

Objectives	2
ACTIVITY 1:	2
ACTIVITY 2:	2
ACTIVITY 3	3
ACTIVITY 4:	3
REFERENCES	3

Note for all questions: You can make as many memory variables as you need

ACTIVITY 1:

Difference of two sets ($S_1 - S_2$) is a set having elements of S_1 which are NOT Present in S_2 , see following examples for detail. Your task is to write a subroutine in Assembly Language that finds Difference of two sets ($S_1 - S_2$). Note that both the sets are sorted and have distinct elements only.

Example 1	Example 2
S_1 : -3, -1, 2, 5, 6, 8, 9 S_2 : -2, 2, 6, 7, 9 Difference: -3, -1, 5, 8	S_1 : -3, -1, 2, 5, 6, 8, 9 S_2 : 1, 3, 7 Difference: -3, -1, 2, 5, 6, 8, 9

ACTIVITY 2:

Initialize **AX** with last 4 digits of your roll number as **Hexadecimal number** (for example, if your roll number is 16L-4195 then **AX** should be initialized with 0x4195). Write a subroutine which receives AX as input and returns number of 1s in AX.

$$n = \text{binary_ones}(\text{Roll \#})$$

For example, # of 1s in 0x 4195 is

$$n = \text{ones}(0x4195) = \text{ones}(0100_0001_1001_0101) = 6$$

ACTIVITY 3

Following table shows a number pyramid (we call it Al-Khwarizmi Pyramid). This pyramid is expanding based on the value of s , its size.

Write a program which uses $s = n + 5$ (n from **Activity 2**) as size of Al-Khwarizmi Pyramid and returns the cumulative sum. For example, if $n = 6$ then $s = 11$, and program should return **506**.

Size (s)	Al-Khwarizmi Pyramid																			Cumulative Sum
1													1							1
2												1	2	1						5
3											1	2	3	2	1					14
4										1	2	3	4	3	2	1				30
5									1	2	3	4	5	4	3	2	1			55
6							1	2	3	4	5	6	5	4	3	2	1			91
7						1	2	3	4	5	6	7	6	5	4	3	2	1		140
8				1	2	3	4	5	6	7	8	7	6	5	4	3	2	1		204
9			1	2	3	4	5	6	7	8	9	8	7	6	5	4	3	2	1	285
10		1	2	3	4	5	6	7	8	9	10	9	8	7	6	5	4	3	2	385
11	1	2	3	4	5	6	7	8	9	10	11	10	9	8	7	6	5	4	3	506

ACTIVITY 4:

Write two subroutines for 16-bit multiplication and 32-bit addition to solve the following problem from Lab4:

Initialize **AX** with last 4 digits of your roll number (for example, if your roll number is 16L-1105 then **AX** should be initialized with 1105). Store \overline{AX} in **BX**. Make a 32-bit memory variable f , initialize it with 0 and compute

$$f = (A \times B) + \{A, B\}$$

\times is **Multiplication** operation, $+$ is **Addition** operation whereas $\{A, B\}$ **concatenates** 16-bit **A** and **B** to form **32-bit** number.

REFERENCES

- ["http://www.dosbox.com/download.php?main=1"](http://www.dosbox.com/download.php?main=1)
- <http://sourceforge.net/projects/nasm>
- <http://www.nasm.us/>
- <http://www.programmersheaven.com/download/21643/download.aspx> (AFD)