

Parallel and Distributed Computing

CS3006

Lecture 13

Basic Communication Operations-III

25th April 2022

Dr. Rana Asif Rehman

All-Reduce

Basic Communication Operations

(All-Reduce)

- Precondition: Every process i has a single message M_i of size m words.
- Post condition: All processes have a reduced message M of size m words.

Strategies:

1. Use **all-to-one reduction** followed by **one-to-all** broadcast ($2 * (t_s + mt_w) \log p$)
2. Use **modified All-to-All comm.** algorithm for hypercube $((t_s + mt_w) \log p)$
 - Replace Union with associative operator

Prefix-Sum

Basic Communication Operations

(Prefix-Sums)


- Prefix-sums are also known as scan operations
- Given p numbers n_0, n_1, \dots, n_{p-1} (one on each node), the problem is to compute the sums such that: -
 - $S_k = \sum_{i=0}^K (n_i)$
 - Here S_k is the prefix-sum computed at k th node after the operation.

Example:


- Original sequence: $\langle 3, 1, 4, 0, 2 \rangle$
- Sequence of prefix sums: $\langle 3, 4, 8, 8, 10 \rangle$

Basic Communication Operations


(Prefix-Sums)




(a) Initial distribution of values



(b) Distribution of sums before second step



(c) Distribution of sums before third step



(d) Final distribution of prefix sums

Basic Communication Operations

(Prefix-Sums)

```
1.  procedure PREFIX_SUMS_HCUBE(my_id, my_number, d, result)
2.  begin
3.      result := my_number;
4.      msg := result;
5.      for i := 0 to d - 1 do
6.          partner := my_id XOR  $2^i$ ;
7.          send msg to partner;
8.          receive number from partner;
9.          msg := msg + number;
10.         if (partner < my_id) then result := result + number;
11.     endfor;
12. end PREFIX_SUMS_HCUBE
```

Algorithm 4.9 Prefix sums on a d -dimensional hypercube.

Scatter and Gather

Basic Communication Operations

(Scatter and Gather)

- Gather is different than reduction as it doesn't reduce the results with associative operator






Figure 4.14 Scatter and gather operations.

Basic Communication Operations


10




(a) Initial distribution of messages



(b) Distribution before the second step



(c) Distribution before the third step



(d) Final distribution of messages

Figure 4.15 The scatter operation on an eight-node hypercube.

All-to-All personalized Communication

11

Basic Communication Operations

12

(All-to-All personalized)

- Each node sends a distinct message of size m to every other node.
- Also known **total exchange**





Figure 4.16 All-to-all personalized communication.

Basic Communication Operations

(All-to-All personalized)



All-to-all personalized communication in transposing a 4 x 4 matrix using four processes.

Basic Communication Operations

(All-to-All personalized [Ring])




Figure 4.18 All-to-all personalized communication on a six-node ring. The label of each message is of the form $\{x, y\}$, where x is the label of the node that originally owned the message, and y is the label of the node that is the final destination of the message. The label $(\{x_1, y_1\}, \{x_2, y_2\}, \dots, \{x_n, y_n\})$ indicates a message that is formed by concatenating n individual messages.

Basic Communication Operations

15

(All-to-All personalized [Ring])


Cost Analysis

$$\begin{aligned} \Rightarrow T &= \sum_{i=1}^{(p-1)} (t_s + (p - i)mt_w) \\ &= \sum_{i=1}^{(p-1)} (t_s) + mt_w \sum_{i=1}^{(p-1)} (p - i) \\ &\rightarrow (p - 1)(t_s) + mt_w \sum_{i=1}^{(p-1)} (i) \\ &\rightarrow \left((t_s + \left(\frac{1}{2}\right) pmt_w) \right) (p - 1) \end{aligned}$$

Basic Communication Operations

(All-to-All personalized [Mesh])

16



(b) Data distribution at the beginning of second phase

Basic Communication Operations

17

(All-to-All personalized [Mesh])


Cost Analysis

- Time for the first phase is identical to that in a ring with \sqrt{p} processors, i.e., $(t_s + t_w mp/2)(\sqrt{p} - 1)$.
 - Here mt_w becomes $\sqrt{p} mt_w$ and P becomes \sqrt{p}
- Time in the second phase is identical to the first phase. Therefore, total time is twice of this time, i.e.,

Basic Communication Operations


(All-to-All personalized [Hyper Cube])

18



(a) Initial distribution of messages

(b) Distribution before the second step



(c) Distribution before the third step

(d) Final distribution of messages

Questions



References

20

1. Kumar, V., Grama, A., Gupta, A., & Karypis, G. (2017). *Introduction to parallel computing*. Redwood City, CA: Benjamin/Cummings.