

Module 3.4: Learning Parameters : Gradient Descent

Now let us see if there is a more efficient and principled way of doing this

Goal

Find a better way of traversing the error surface so that we can reach the minimum value quickly without resorting to brute force search!

vector of parameters,
say, randomly initialized

$$\theta = [w, b]$$

vector of parameters,
say, randomly initial-
ized

$$\theta = [w, b]$$


$$\Delta\theta = [\Delta w, \Delta b]$$

change in the
values of w, b

vector of parameters,
say, randomly initial-
ized

$$\theta = [w, b]$$

change in the
values of w, b




vector of parameters,
say, randomly initial-
ized

$$\theta = [w, b]$$

$$\Delta\theta = [\Delta w, \Delta b]$$

change in the
values of w, b




vector of parameters,
say, randomly initialized

$$\theta = [w, b]$$

change in the
values of w, b

$$\Delta\theta = [\Delta w, \Delta b]$$




We moved in the direction of $\Delta\theta$

vector of parameters,
say, randomly initialized

$$\theta = [w, b]$$

change in the
values of w, b



We moved in the direction of $\Delta\theta$


Let us be a bit conservative:
move only by a small amount η

vector of parameters,
say, randomly initialized

$$\theta = [w, b]$$

change in the
values of w, b

$$\Delta\theta = [\Delta w, \Delta b]$$



We moved in the direction of $\Delta\theta$


Let us be a bit conservative: move only by a small amount η

vector of parameters,
say, randomly initialized

$$\theta = [w, b]$$

change in the
values of w, b

$$\Delta\theta = [\Delta w, \Delta b]$$



We moved in the direction of $\Delta\theta$


Let us be a bit conservative: move only by a small amount η

vector of parameters,
say, randomly initialized

$$\theta = [w, b]$$

change in the
values of w, b

$$\theta_{new} = \theta + \eta \cdot \Delta\theta$$



We moved in the direction of $\Delta\theta$


Let us be a bit conservative: move only by a small amount η

vector of parameters,
say, randomly initialized

$$\theta = [w, b]$$

change in the
values of w, b

$$\Delta\theta = [\Delta w, \Delta b]$$



We moved in the direction of $\Delta\theta$

Let us be a bit conservative: move only by a small amount η


Question: What is the right $\Delta\theta$ to use ?

vector of parameters,
say, randomly initialized

$$\theta = [w, b]$$

change in the
values of w, b

$$\Delta\theta = [\Delta w, \Delta b]$$



We moved in the direction of $\Delta\theta$

Let us be a bit conservative: move only by a small amount η

$$\theta_{new} = \theta + \eta \cdot \Delta\theta$$

Question: What is the right $\Delta\theta$ to use?

The answer comes from Taylor series

For ease of notation, let $\Delta\theta = u$, then from Taylor series, we have,

For ease of notation, let $\Delta\theta = u$, then from Taylor series, we have,

$$\mathcal{L}(\theta + \eta u) = \mathcal{L}(\theta) + \eta * u^T \nabla \mathcal{L}(\theta) + \frac{\eta^2}{2!} * u^T \nabla^2 \mathcal{L}(\theta) u + \frac{\eta^3}{3!} * \dots + \frac{\eta^4}{4!} * \dots$$

For ease of notation, let $\Delta\theta = u$, then from Taylor series, we have,

$$\begin{aligned}\mathcal{L}(\theta + \eta u) &= \mathcal{L}(\theta) + \eta * u^T \nabla \mathcal{L}(\theta) + \frac{\eta^2}{2!} * u^T \nabla^2 \mathcal{L}(\theta) u + \frac{\eta^3}{3!} * \dots + \frac{\eta^4}{4!} * \dots \\ &= \mathcal{L}(\theta) + \eta * u^T \nabla \mathcal{L}(\theta) [\eta \text{ is typically small, so } \eta^2, \eta^3, \dots \rightarrow 0]\end{aligned}$$

For ease of notation, let $\Delta\theta = u$, then from Taylor series, we have,

$$\begin{aligned}\mathcal{L}(\theta + \eta u) &= \mathcal{L}(\theta) + \eta * u^T \nabla \mathcal{L}(\theta) + \frac{\eta^2}{2!} * u^T \nabla^2 \mathcal{L}(\theta) u + \frac{\eta^3}{3!} * \dots + \frac{\eta^4}{4!} * \dots \\ &= \mathcal{L}(\theta) + \eta * u^T \nabla \mathcal{L}(\theta) [\eta \text{ is typically small, so } \eta^2, \eta^3, \dots \rightarrow 0]\end{aligned}$$

Note that the move (ηu) would be favorable only if,

$$\mathcal{L}(\theta + \eta u) - \mathcal{L}(\theta) < 0 \text{ [i.e., if the new loss is less than the previous loss]}$$

For ease of notation, let $\Delta\theta = u$, then from Taylor series, we have,

$$\begin{aligned}\mathcal{L}(\theta + \eta u) &= \mathcal{L}(\theta) + \eta * u^T \nabla \mathcal{L}(\theta) + \frac{\eta^2}{2!} * u^T \nabla^2 \mathcal{L}(\theta) u + \frac{\eta^3}{3!} * \dots + \frac{\eta^4}{4!} * \dots \\ &= \mathcal{L}(\theta) + \eta * u^T \nabla \mathcal{L}(\theta) [\eta \text{ is typically small, so } \eta^2, \eta^3, \dots \rightarrow 0]\end{aligned}$$

Note that the move (ηu) would be favorable only if,

$$\mathcal{L}(\theta + \eta u) - \mathcal{L}(\theta) < 0 \text{ [i.e., if the new loss is less than the previous loss]}$$

This implies,

$$u^T \nabla \mathcal{L}(\theta) < 0$$

Okay, so we have,

$$u^T \nabla \mathcal{L}(\theta) < 0$$

But, what is the range of $u^T \nabla \mathcal{L}(\theta)$?

Okay, so we have,

$$u^T \nabla \mathcal{L}(\theta) < 0$$

But, what is the range of $u^T \nabla \mathcal{L}(\theta)$? Let us see....

Okay, so we have,

$$u^T \nabla \mathcal{L}(\theta) < 0$$

But, what is the range of $u^T \nabla \mathcal{L}(\theta)$? Let us see....

Let β be the angle between u^T and $\nabla \mathcal{L}(\theta)$, then we know that,

Okay, so we have,

$$u^T \nabla \mathcal{L}(\theta) < 0$$

But, what is the range of $u^T \nabla \mathcal{L}(\theta)$? Let us see....

Let β be the angle between u^T and $\nabla \mathcal{L}(\theta)$, then we know that,

$$-1 \leq \cos(\beta) = \frac{u^T \nabla \mathcal{L}(\theta)}{\|u\| * \|\nabla \mathcal{L}(\theta)\|} \leq 1$$

Okay, so we have,

$$u^T \nabla \mathcal{L}(\theta) < 0$$

But, what is the range of $u^T \nabla \mathcal{L}(\theta)$? Let us see....

Let β be the angle between u^T and $\nabla \mathcal{L}(\theta)$, then we know that,

$$-1 \leq \cos(\beta) = \frac{u^T \nabla \mathcal{L}(\theta)}{\|u\| * \|\nabla \mathcal{L}(\theta)\|} \leq 1$$

Okay, so we have,

$$u^T \nabla \mathcal{L}(\theta) < 0$$

But, what is the range of $u^T \nabla \mathcal{L}(\theta)$? Let us see....

Let β be the angle between u^T and $\nabla \mathcal{L}(\theta)$, then we know that,

$$-1 \leq \cos(\beta) = \frac{u^T \nabla \mathcal{L}(\theta)}{\|u\| * \|\nabla \mathcal{L}(\theta)\|} \leq 1$$

multiply throughout by $k = \|u\| * \|\nabla \mathcal{L}(\theta)\|$

$$-k \leq k * \cos(\beta) = u^T \nabla \mathcal{L}(\theta) \leq k$$

Okay, so we have,

$$u^T \nabla \mathcal{L}(\theta) < 0$$

But, what is the range of $u^T \nabla \mathcal{L}(\theta)$? Let us see....

Let β be the angle between u^T and $\nabla \mathcal{L}(\theta)$, then we know that,

$$-1 \leq \cos(\beta) = \frac{u^T \nabla \mathcal{L}(\theta)}{\|u\| * \|\nabla \mathcal{L}(\theta)\|} \leq 1$$

multiply throughout by $k = \|u\| * \|\nabla \mathcal{L}(\theta)\|$

$$-k \leq k * \cos(\beta) = u^T \nabla \mathcal{L}(\theta) \leq k$$

Thus, $\mathcal{L}(\theta + \eta u) - \mathcal{L}(\theta) = u^T \nabla \mathcal{L}(\theta) = k * \cos(\beta)$ will be most negative when $\cos(\beta) = -1$ i.e., when β is 180°

Gradient Descent Rule

- The direction u that we intend to move in should be at 180° w.r.t. the gradient

Gradient Descent Rule

- The direction u that we intend to move in should be at 180° w.r.t. the gradient
- In other words, move in a direction opposite to the gradient

Gradient Descent Rule

- The direction u that we intend to move in should be at 180° w.r.t. the gradient
- In other words, move in a direction opposite to the gradient

Parameter Update Equations

$$w_{t+1} = w_t - \eta \nabla w_t$$

$$b_{t+1} = b_t - \eta \nabla b_t$$

where, $\nabla w_t = \frac{\partial \mathcal{L}(w, b)}{\partial w}$ at $w = w_t, b = b_t$, $\nabla b = \frac{\partial \mathcal{L}(w, b)}{\partial b}$ at $w = w_t, b = b_t$

Gradient Descent Rule

- The direction u that we intend to move in should be at 180° w.r.t. the gradient
- In other words, move in a direction opposite to the gradient

Parameter Update Equations

$$w_{t+1} = w_t - \eta \nabla w_t$$

$$b_{t+1} = b_t - \eta \nabla b_t$$

where, $\nabla w_t = \frac{\partial \mathcal{L}(w, b)}{\partial w}$ at $w = w_t, b = b_t$, $\nabla b = \frac{\partial \mathcal{L}(w, b)}{\partial b}$ at $w = w_t, b = b_t$

So we now have a more principled way of moving in the w - b plane than our “guess work” algorithm


- Let us create an algorithm from this rule ...

- Let us create an algorithm from this rule ...


Algorithm: gradient_descent()


```
t ← 0;  
max_iterations ← 1000;  
while  $t < max\_iterations$  do  
    |  $w_{t+1} \leftarrow w_t - \eta \nabla w_t;$   
    |  $b_{t+1} \leftarrow b_t - \eta \nabla b_t;$   
end
```

- To see this algorithm in practice let's first derive ∇w and ∇b for our toy neural network




$$f(x) = \frac{1}{1+e^{-(w \cdot x + b)}}$$







$$f(x) = \frac{1}{1+e^{-(w \cdot x + b)}}$$

Let's assume there is only 1 point to fit
 (x, y)






$$f(x) = \frac{1}{1+e^{-(w \cdot x + b)}}$$




Let's assume there is only 1 point to fit
 (x, y)

$$\mathcal{L}(w, b) = \frac{1}{2} * (f(x) - y)^2$$



$$f(x) = \frac{1}{1+e^{-(w \cdot x + b)}}$$



Let's assume there is only 1 point to fit
 (x, y)

$$\mathcal{L}(w, b) = \frac{1}{2} * (f(x) - y)^2$$

$$\nabla_w = \frac{\partial \mathcal{L}(w, b)}{\partial w} = \frac{\partial}{\partial w} \left[\frac{1}{2} * (f(x) - y)^2 \right]$$

$$\nabla w = \frac{\partial}{\partial w} \left[\frac{1}{2} * (f(x) - y)^2 \right]$$

$$\begin{aligned}\nabla w &= \frac{\partial}{\partial w} \left[\frac{1}{2} * (f(x) - y)^2 \right] \\ &= \frac{1}{2} * [2 * (f(x) - y) * \frac{\partial}{\partial w} (f(x) - y)]\end{aligned}$$

$$\begin{aligned}\nabla w &= \frac{\partial}{\partial w} \left[\frac{1}{2} * (f(x) - y)^2 \right] \\ &= \frac{1}{2} * [2 * (f(x) - y) * \frac{\partial}{\partial w} (f(x) - y)] \\ &= (f(x) - y) * \frac{\partial}{\partial w} (f(x))\end{aligned}$$

$$\begin{aligned}\nabla w &= \frac{\partial}{\partial w} \left[\frac{1}{2} * (f(x) - y)^2 \right] \\&= \frac{1}{2} * [2 * (f(x) - y) * \frac{\partial}{\partial w} (f(x) - y)] \\&= (f(x) - y) * \frac{\partial}{\partial w} (f(x)) \\&= (f(x) - y) * \frac{\partial}{\partial w} \left(\frac{1}{1 + e^{-(wx+b)}} \right)\end{aligned}$$

$$\begin{aligned}
 \nabla w &= \frac{\partial}{\partial w} \left[\frac{1}{2} * (f(x) - y)^2 \right] \\
 &= \frac{1}{2} * [2 * (f(x) - y) * \frac{\partial}{\partial w} (f(x) - y)] \\
 &= (f(x) - y) * \frac{\partial}{\partial w} (f(x)) \\
 &= (f(x) - y) * \frac{\partial}{\partial w} \left(\frac{1}{1 + e^{-(wx+b)}} \right)
 \end{aligned}$$

$$\frac{\partial}{\partial w} \left(\frac{1}{1 + e^{-(wx+b)}} \right)$$

$$\begin{aligned}
 \nabla w &= \frac{\partial}{\partial w} \left[\frac{1}{2} * (f(x) - y)^2 \right] \\
 &= \frac{1}{2} * [2 * (f(x) - y) * \frac{\partial}{\partial w} (f(x) - y)] \\
 &= (f(x) - y) * \frac{\partial}{\partial w} (f(x)) \\
 &= (f(x) - y) * \frac{\partial}{\partial w} \left(\frac{1}{1 + e^{-(wx+b)}} \right)
 \end{aligned}$$

$$\begin{aligned}
 &\frac{\partial}{\partial w} \left(\frac{1}{1 + e^{-(wx+b)}} \right) \\
 &= \frac{-1}{(1 + e^{-(wx+b)})^2} \frac{\partial}{\partial w} (e^{-(wx+b)})
 \end{aligned}$$

$$\begin{aligned}
 \nabla w &= \frac{\partial}{\partial w} \left[\frac{1}{2} * (f(x) - y)^2 \right] \\
 &= \frac{1}{2} * [2 * (f(x) - y) * \frac{\partial}{\partial w} (f(x) - y)] \\
 &= (f(x) - y) * \frac{\partial}{\partial w} (f(x)) \\
 &= (f(x) - y) * \frac{\partial}{\partial w} \left(\frac{1}{1 + e^{-(wx+b)}} \right)
 \end{aligned}$$

$$\begin{aligned}
 &\frac{\partial}{\partial w} \left(\frac{1}{1 + e^{-(wx+b)}} \right) \\
 &= \frac{-1}{(1 + e^{-(wx+b)})^2} \frac{\partial}{\partial w} (e^{-(wx+b)}) \\
 &= \frac{-1}{(1 + e^{-(wx+b)})^2} * (e^{-(wx+b)}) \frac{\partial}{\partial w} (-wx - b)
 \end{aligned}$$

$$\begin{aligned}
 \nabla w &= \frac{\partial}{\partial w} \left[\frac{1}{2} * (f(x) - y)^2 \right] \\
 &= \frac{1}{2} * [2 * (f(x) - y) * \frac{\partial}{\partial w} (f(x) - y)] \\
 &= (f(x) - y) * \frac{\partial}{\partial w} (f(x)) \\
 &= (f(x) - y) * \frac{\partial}{\partial w} \left(\frac{1}{1 + e^{-(wx+b)}} \right)
 \end{aligned}$$


$$\begin{aligned}
 &\frac{\partial}{\partial w} \left(\frac{1}{1 + e^{-(wx+b)}} \right) \\
 &= \frac{-1}{(1 + e^{-(wx+b)})^2} \frac{\partial}{\partial w} (e^{-(wx+b)}) \\
 &= \frac{-1}{(1 + e^{-(wx+b)})^2} * (e^{-(wx+b)}) \frac{\partial}{\partial w} (-wx - b) \\
 &= \frac{-1}{(1 + e^{-(wx+b)})} * \frac{e^{-(wx+b)}}{(1 + e^{-(wx+b)})} * (-x) \\
 &= \frac{1}{(1 + e^{-(wx+b)})} * \frac{e^{-(wx+b)}}{(1 + e^{-(wx+b)})} * (x)
 \end{aligned}$$

$$\begin{aligned}
 \nabla w &= \frac{\partial}{\partial w} \left[\frac{1}{2} * (f(x) - y)^2 \right] \\
 &= \frac{1}{2} * [2 * (f(x) - y) * \frac{\partial}{\partial w} (f(x) - y)] \\
 &= (f(x) - y) * \frac{\partial}{\partial w} (f(x)) \\
 &= (f(x) - y) * \frac{\partial}{\partial w} \left(\frac{1}{1 + e^{-(wx+b)}} \right)
 \end{aligned}$$

$$\begin{aligned}
 &\frac{\partial}{\partial w} \left(\frac{1}{1 + e^{-(wx+b)}} \right) \\
 &= \frac{-1}{(1 + e^{-(wx+b)})^2} \frac{\partial}{\partial w} (e^{-(wx+b)}) \\
 &= \frac{-1}{(1 + e^{-(wx+b)})^2} * (e^{-(wx+b)}) \frac{\partial}{\partial w} (-wx - b) \\
 &= \frac{-1}{(1 + e^{-(wx+b)})} * \frac{e^{-(wx+b)}}{(1 + e^{-(wx+b)})} * (-x) \\
 &= \frac{1}{(1 + e^{-(wx+b)})} * \frac{e^{-(wx+b)}}{(1 + e^{-(wx+b)})} * (x) \\
 &= f(x) * (1 - f(x)) * x
 \end{aligned}$$


$$\begin{aligned}
\nabla w &= \frac{\partial}{\partial w} \left[\frac{1}{2} * (f(x) - y)^2 \right] \\
&= \frac{1}{2} * [2 * (f(x) - y) * \frac{\partial}{\partial w} (f(x) - y)] \\
&= (f(x) - y) * \frac{\partial}{\partial w} (f(x)) \\
&= (f(x) - y) * \frac{\partial}{\partial w} \left(\frac{1}{1 + e^{-(wx+b)}} \right) \\
&= \color{red}{(f(x) - y) * f(x) * (1 - f(x)) * x}
\end{aligned}$$


$$\begin{aligned}
&\frac{\partial}{\partial w} \left(\frac{1}{1 + e^{-(wx+b)}} \right) \\
&= \frac{-1}{(1 + e^{-(wx+b)})^2} \frac{\partial}{\partial w} (e^{-(wx+b)}) \\
&= \frac{-1}{(1 + e^{-(wx+b)})^2} * (e^{-(wx+b)}) \frac{\partial}{\partial w} (-wx - b) \\
&= \frac{-1}{(1 + e^{-(wx+b)})} * \frac{e^{-(wx+b)}}{(1 + e^{-(wx+b)})} * (-x) \\
&= \frac{1}{(1 + e^{-(wx+b)})} * \frac{e^{-(wx+b)}}{(1 + e^{-(wx+b)})} * (x) \\
&= f(x) * (1 - f(x)) * x
\end{aligned}$$




$$f(x) = \frac{1}{1+e^{-(w \cdot x + b)}}$$

So if there is only 1 point (x, y) , we have,






$$f(x) = \frac{1}{1+e^{-(w \cdot x + b)}}$$




So if there is only 1 point (x, y) , we have,

$$\nabla w = (f(x) - y) * f(x) * (1 - f(x)) * x$$




$$f(x) = \frac{1}{1+e^{-(w \cdot x + b)}}$$




So if there is only 1 point (x, y) , we have,

$$\nabla w = (f(x) - y) * f(x) * (1 - f(x)) * x$$

For two points,



$$f(x) = \frac{1}{1+e^{-(w \cdot x + b)}}$$




So if there is only 1 point (x, y) , we have,


$$\nabla w = (f(x) - y) * f(x) * (1 - f(x)) * x$$

For two points,

$$\nabla w = \sum_{i=1}^2 (f(x_i) - y_i) * f(x_i) * (1 - f(x_i)) * x_i$$



$$f(x) = \frac{1}{1+e^{-(w \cdot x + b)}}$$



So if there is only 1 point (x, y) , we have,

$$\nabla w = (f(x) - y) * f(x) * (1 - f(x)) * x$$

For two points,

$$\nabla w = \sum_{i=1}^2 (f(x_i) - y_i) * f(x_i) * (1 - f(x_i)) * x_i$$

$$\nabla b = \sum_{i=1}^2 (f(x_i) - y_i) * f(x_i) * (1 - f(x_i))$$

```
X = [0.5, 2.5]  
Y = [0.2, 0.9]
```

```
X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))
```

```
X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err
```

```



X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err

```

Random search on error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]



def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err

def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

```

Random search on error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))



def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err

def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

```

Random search on error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Random search on error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

[X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



```

X = [0.5, 2.5]
Y = [0.2, 0.9]

def f(w,b,x) : #sigmoid with parameters w,b
    return 1.0 / (1.0 + np.exp(-(w*x + b)))

def error (w, b) :
    err = 0.0
    for x,y in zip(X,Y) :
        fx = f(w,b,x)
        err += 0.5 * (fx - y) ** 2
    return err



def grad_b(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx)

def grad_w(w,b,x,y) :
    fx = f(w,b,x)
    return (fx - y) * fx * (1 - fx) * x

def do_gradient_descent() :
    w, b, eta, max_epochs = -2, -2, 1.0, 1000
    for i in range(max_epochs) :
        dw, db = 0, 0
        for x,y in zip(X, Y) :
            dw += grad_w(w, b, x, y)
            db += grad_b(w, b, x, y)
        w = w - eta * dw
        b = b - eta * db

```

Gradient descent on the error surface



- Later on in the course we will look at gradient descent in much more detail and discuss its variants

- Later on in the course we will look at gradient descent in much more detail and discuss its variants
- For the time being it suffices to know that we have an algorithm for learning the parameters of a sigmoid neuron

- Later on in the course we will look at gradient descent in much more detail and discuss its variants
- For the time being it suffices to know that we have an algorithm for learning the parameters of a sigmoid neuron
- So where do we head from here ?