

# Lab 3

Muyuan Zhang


2022-11-11

## Visualizing Timing Data

- Run the program and record the average time for `contains()` on 11 set sizes: 210, 211, 212... 219, 220.
- Time `contains()` several thousand times for each set size, and take the average.
- Plot these times against the set size.

```
library(ggplot2)
size <- c(1024, 2048, 4096, 8192, 16384, 32768, 65536, 131072, 262144, 524288, 1048576)
avgttime <- c(2406.64, 1991.2, 2305.01, 685.85, 555.42, 590.82, 830.0, 955.82, 1942.49, 3219.21, 6627.5)
timeingdata <- data.frame(size, avgttime)
ggplot(timeingdata, aes(size, avgttime)) + geom_line() + geom_point() + labs(
  x = "size of set",
  y = "average time / nanosecond",
  title = "Average Run Time of contains() On A SortedSet")
```

Average Run Time of contains() On A SortedSet



When the size goes above 16000, size-avgttime is almost linear. The left part of the graph is too crowded so we can try to apply a base-10 logarithmic transformation of x axis (size) as below.

```
ggplot(timeingdata, aes(size, avgttime)) + geom_line() + geom_point() + scale_x_log10() + labs(  
  x = "size of set (base-10 log)",  
  y = "average time / nanosecond",  
  title = "Average Run Time of contains() On A SortedSet, x-axis Base-10 Log")
```

Average Run Time of contains() On A SortedSet, x-axis Base-10 Log

