

Hole Filling



"Make it Real"



A Lithograph of a Waterfall

An Oil Painting of an Old Man

HW5 Part A: The Power of Diffusion Models!

COMS4732: Computer Vision 2

Part B

Due: Friday, April 17 11:59pm PT

WE RECOMMEND USING GPUS FROM COLAB TO FINISH THIS PROJECT! (STUDENTS GET COLAB PRO FOR FREE)!

Starter code can be found here.

Collapse all

▼ Overview

In part A you will play around with diffusion models, implement diffusion sampling loops, and use them for other tasks such as inpainting and creating optical illusions. Instructions can be found below and in the starter code above.

Because part A is simply to get your feet wet with pre-trained diffusion models, all deliverables should be completed in the notebook. You will still submit a webpage with your results.

Note: Implementations are provided for parts 1.1, 1.2, 1.3, and 1.4. You can find versions of the starter code with and without these parts implemented at the link above. **You are still expected to submit images for those sections** but are just not required to implement them yourselves.

▼ Part 0: Setup

Gaining Access to DeepFloyd

We are going to use the DeepFloyd IF diffusion model. DeepFloyd is a two stage model trained by Stability AI. The first stage produces images of size 64×64 and the second stage takes the outputs of the first stage and generates images of size 256×256. We provide upsampling code at the very end of the notebook, though this is not required in your submission. Before using DeepFloyd, you must accept its usage conditions. To do so:

1. Make a Hugging Face account and log in.
2. Accept the license on the model card of DeepFloyd/IF-I-XL-v1.0. For affiliation, you can fill in "The University of California, Berkeley." Accepting the license on the stage I model card will auto accept for the other IF models.
3. Log in locally by entering your Hugging Face Hub access token below. You should be able to find and create tokens here. A read token is enough for this project.

Play with the Model using Your Own Text Prompts!

DeepFloyd was trained as a text-to-image model, which takes text prompts as input and outputs images that are aligned with the text. However, a raw text string cannot be directly used as the model's input — we first need to convert it into a high-dimensional vector (of 4096 dimensions in our case) that the model can understand, a.k.a. prompt embeddings.

Since prompt encoders are always very big and hard to run in your notebook, we provide two Huggingface clusters A and B for generating your own prompt embeddings! Both are the same and feel free to use either of them. Please follow their instructions to create a dictionary of embeddings for your prompts, download the resulting `.pth` file, and load it in Google Colab.

Please note that both clusters have daily usage limits, so if you're unable to use one, please try another or try again tomorrow. Alternatively, **START EARLY** and download the `.pth` file in advance — you only need to generate it once, and you can reuse the downloaded file afterward. If the official site experiences issues or runs out of computation, you can download one of our precomputed embeddings, but this is a predefined set of prompts and lacks flexibility. We want to see your creativity!

Deliverables

- Come up with some interesting text prompts and generate their embeddings.
- Choose 3 of your prompts to generate images and display the caption and the output of the model. Reflect on the quality of the outputs and their relationships to the text prompts. Make sure to try at least 2 different `num_inference_steps` values.
- Report the random seed that you're using here. You should use the same seed all subsequent parts.

Hint

- Since we ask you to generate visual anagrams and hybrid images, you may want to include several text pairs that you plan to use for those tasks later.

▼ Part 1: Sampling Loops

In this part of the problem set, you will write your own “sampling loops” that use the pretrained DeepFloyd denoisers. These should produce high quality images such as the ones generated above.

You will then modify these sampling loops to solve different tasks such as inpainting or producing optical illusions.

Diffusion Models Primer

Starting with a clean image, x_0, we can iteratively add noise to an image, obtaining progressively more and more noisy versions of the image, x_t, until we're left with basically pure noise at timestep $t = T$. When $t = 0$, we have a clean image, and for larger t more noise is in the image.

A diffusion model tries to reverse this process by denoising the image. By giving a diffusion model a noisy x_t and the timestep t, the model predicts the noise in the image. With the predicted noise, we can either completely remove the noise from the image, to obtain an estimate of x_0, or we can remove just a portion of the noise, obtaining an estimate of x_{t-1}, with slightly less noise.

To generate images from the diffusion model (sampling), we start with pure noise at timestep T sampled from a gaussian distribution, which we denote x_T. We can then predict and remove part of the noise, giving us x_{T-1}. Repeating this process until we arrive at x_0 gives us a clean image.

For the DeepFloyd models, $T = 1000$.

The exact amount of noise added at each step is dictated by noise coefficients, $\bar{\alpha}_t$, which were chosen by the people who trained DeepFloyd.

▶ 1.1 Implementing the Forward Process (Implementation Provided)

▶ 1.2 Classical Denoising (Implementation Provided)

▶ 1.3 One-Step Denoising (Implementation Provided)

▶ 1.4 Iterative Denoising (Implementation Provided)

1.5 Diffusion Model Sampling

In part 1.4, we use the diffusion model to denoise an image. Another thing we can do with the `iterative_denoise` function is to generate images from scratch. We can do this by setting `i_start = 0` and passing `im_noisy` as random noise. This effectively denoises pure noise. Please do this, and show 5 results of the prompt `"a high quality photo"`.

Deliverables

- Show 5 sampled images.

Hints

- Use `torch.randn` to make the noise.
- Make sure you move the tensor to the correct device and correct data type by calling `.half()` and `.to(device)`.
- The quality of the images will not be spectacular, but should be reasonable images. We will fix this in the next section with CFG.



Sample 1



Sample 2

Sample 3

Sample 4

Sample 5

1.6 Classifier-Free Guidance (CFG)

You may have noticed that the generated images in the prior section are not very good, and some are completely non-sensical. In order to greatly improve image quality (at the expense of image diversity), we can use a technicque called Classifier-Free Guidance.

In CFG, we compute both a conditional and an unconditional noise estimate. We denote these ϵ_c and ϵ_u. Then, we let our new noise estimate be:

$$\epsilon = \epsilon_u + \gamma(\epsilon_c - \epsilon_u) \tag{A.4}$$

where γ controls the strength of CFG. Notice that for $\gamma = 0$, we get an unconditional noise estimate, and for $\gamma = 1$ we get the conditional noise estimate. The magic happens when $\gamma > 1$. In this case, we get much higher quality images. Why this happens is still up to vigorous debate. For more information on CFG, you can check out this blog post.

Please implement the `iterative_denoise_cfg` function, identical to the `iterative_denoise` function but using classifier-free guidance. To get an unconditional noise estimate, we can just pass an empty prompt embedding to the diffusion model (the model was trained to predict an unconditional noise estimate when given an empty text prompt).

Disclaimer Disclaimer Before, we used `"a high quality photo"` as a "null" condition. Now, we will use the actual `""` null prompt for unconditional guidance for CFG. In the later part, you should always use `""` null prompt for unconditional guidance.

Deliverables

- Implement the `iterative_denoise_cfg` function
- Show 5 images of `"a high quality photo"` with a CFG scale of $\gamma = 7$. Now this prompt becomes a **condition** (but fairly weak) to generate **conditional** noise! You will use your customized prompts as stronger conditions in part 1.7 - part 1.9.

Hints

- You will need to run the UNet twice, once for the conditional prompt embedding, and once for the unconditional
- The UNet will predict both a conditional and an unconditional variance. Just use the conditional variance with the `add_variance` function.
- The resulting images should be much better than those in the prior section.

Sample 1 with CFG

Sample 2 with CFG

Sample 3 with CFG

Sample 4 with CFG

Sample 5 with CFG

1.7 Image-to-image Translation

Note: You should use CFG from this point forward.

In part 1.4, we take a real image, add noise to it, and then denoise. This effectively allows us to make edits to existing images. The more noise we add, the larger the edit will be. This works because in order to denoise an image, the diffusion model must to some extent "hallucinate" new things -- the model has to be "creative." Another way to think about it is that the denoising process "forces" a noisy image back onto the manifold of natural images.

Here, we're going to take the original Campanile image, noise it a little, and force it back onto the image manifold without any conditioning. Effectively, we're going to get an image that is similar to the Campanile (with a low-enough noise level). This follows the SDEdit algorithm.

To start, please run the forward process to get a noisy Campanile, and then run the `iterative_denoise_cfg` function using a starting index of [1, 3, 5, 7, 10, 20] steps and show the results, labeled with the starting index. You should see a series of "edits" to the original image, gradually matching the original image closer and closer.

Deliverables

- Edits of the Campanile image, using the given prompt at noise levels [1, 3, 5, 7, 10, 20] with the conditional text prompt `"a high quality photo"`
- Edits of 2 of your own test images, using the same procedure.

Hints

- You should have a range of images, gradually looking more like the original image

SDEdit with

SDEdit with

SDEdit with

SDEdit with

SDEdit with

SDEdit with

`i_start=1` `i_start=3` `i_start=5` `i_start=7` `i_start=10` `i_start=20`

Campanile

1.7.1 Editing Hand-Drawn and Web Images

This procedure works particularly well if we start with a nonrealistic image (e.g. painting, a sketch, some scribbles) and project it onto the natural image manifold.

Please experiment by starting with hand-drawn or other non-realistic images and see how you can get them onto the natural image manifold in fun ways.

We provide you with 2 ways to provide inputs to the model:

1. Download images from the web
2. Draw your own images

Please find an image from the internet and apply edits exactly as above. And also draw your own images, and apply edits exactly as above. Feel free to copy the prior cell here. For drawing inspiration, you can check out the examples on this project page.

Deliverables

- 1 image from the web of your choice, edited using the above method for noise levels [1, 3, 5, 7, 10, 20] (and whatever additional noise levels you want)
- 2 hand drawn images, edited using the above method for noise levels [1, 3, 5, 7, 10, 20] (and whatever additional noise levels you want)

Hints

- We provide you with preprocessing code to convert web images to the format expected by DeepFloyd
- Unfortunately, the drawing interface is hardcoded to be 300x600 pixels, but we need a square image. The code will center crop, so just draw in the middle of the canvas.

Avocado at `i_start=1`

Avocado at `i_start=3`

Avocado at `i_start=5`



Avocado at `i_start=7`

Avocado at `i_start=10`



Avocado at `i_start=20`

Avocado

House at `i_start=1`

House at `i_start=3`

House at `i_start=5`

House at `i_start=7`

House at `i_start=10`

House at `i_start=20`

Original House Sketch

1.7.2 Inpainting

We can use the same procedure to implement inpainting (following the RePaint paper). That is, given an image x_{orig}, and a binary mask $\mathbf{m}$, we can create a new image that has the same content where $\mathbf{m}$ is 0, but new content wherever $\mathbf{m}$ is 1.

To do this, we can run the diffusion denoising loop. But at every step, after obtaining x_t, we "force" x_t to have the same pixels as x_{orig} where $\mathbf{m}$ is 0, i.e.:

$$x_t \leftarrow \mathbf{m}x_t + (1 - \mathbf{m})\text{forward}(x_{orig}, t) \tag{A.5}$$

Essentially, we leave everything inside the edit mask alone, but we replace everything outside the edit mask with our original image -- with the correct amount of noise added for timestep t.

Please implement this below, and edit the picture to inpaint the top of the Campanile.

Deliverables

- A properly implemented `inpaint` function
- The Campanile inpainted (feel free to use your own mask)
- 2 of your own images edited (come up with your own mask)
  - look at the results from this paper for inspiration

Hints

- Reuse the `forward` function you implemented earlier to implement inpainting
- Because we are using the diffusion model for tasks it was not trained for, you may have to run the sampling process a few times before you get a nice result.
- You can copy and paste your iterative_denoise_cfg function. To get inpainting to work should only require (roughly) 1-2 additional lines and a few small changes.

Campanile | Mask | Hole to Fill | Campanile Inpainted

1.7.3 Text-Conditional Image-to-image Translation

Now, we will do the same thing as SDEdit, but guide the projection with a text prompt. This is no longer pure "projection to the natural image manifold" but also adds control using language. This is simply a matter of changing the prompt from `"a high quality photo"` to any of your prompt!

Deliverables

- Edits of the Campanile, using the given prompt at noise levels [1, 3, 5, 7, 10, 20]
- Edits of 2 of your own test images, using the same procedure

Hints

- The images should gradually look more like original image, but also look like the text prompt.

Rocket Ship at noise level 1

Rocket Ship at noise level 3

Rocket Ship at noise level 5

Rocket Ship at noise level 7

Rocket Ship at noise level 10

Rocket Ship at noise level 20

Campanile

1.8 Visual Anagrams

In this part, we are finally ready to implement Visual Anagrams and create optical illusions with diffusion models. In this part, we will create an image that looks like `"an oil painting of people around a campfire"`, but when flipped upside down will reveal `"an oil painting of an old man"`.

To do this, we will denoise an image x_t at step t normally with the prompt p_1, to obtain noise estimate ϵ_1. But at the same time, we will flip x_t upside down, and denoise with the prompt p_2, to get noise estimate ϵ_2. We can flip ϵ_2 back, and average the two noise estimates. We can then perform a reverse/denoising diffusion step with the averaged noise estimate.

The full algorithm will be:

$$\epsilon_1 = \text{CFG of UNet}(x_t, t, p_1)$$

$$\epsilon_2 = \text{flip}(\text{CFG of UNet}(\text{flip}(x_t), t, p_2))$$

$$\epsilon = (\epsilon_1 + \epsilon_2)/2$$

where UNet is the diffusion model UNet from before, $\text{flip}(\cdot)$ is a function that flips the image, and p_1 and p_2 are two different text prompt embeddings. And our final noise estimate is ϵ. Please implement the above algorithm and show example of an illusion.

Deliverables

- Correctly implemented `visual_anagrams` function
- 2 illusions of your choice that change appearance when you flip it upside down (feel free to take inspirations from this page).

Hints

- You may have to run multiple times to get a really good result for the same reasons as above.

An Oil Painting of an Old Man

An Oil Painting of People around a Campfire

1.9 Hybrid Images

In this part we'll implement Factorized Diffusion and create hybrid images just like in project 2.

In order to create hybrid images with a diffusion model we can use a similar technique as above. We will create a composite noise estimate ϵ, by estimating the noise with two different text prompts, and then combining low frequencies from one noise estimate with high frequencies of the other. The algorithm is:

$$\epsilon_1 = \text{CFG of UNet}(x_t, t, p_1)$$

$$\epsilon_2 = \text{CFG of UNet}(x_t, t, p_2)$$

$$\epsilon = f_{\text{lowpass}}(\epsilon_1) + f_{\text{highpass}}(\epsilon_2)$$

where UNet is the diffusion model UNet, f_{lowpass} is a low pass function, f_{highpass} is a high pass function, and p_1 and p_2 are two different text prompt embeddings. Our final noise estimate is ϵ. Please show an example of a hybrid image using this technique (you may have to run multiple times to get a really good result for the same reasons as above). We recommend that you use a gaussian blur of kernel size 33 and sigma 2.

Deliverables

- Correctly implemented `make_hybrids` function
- 2 hybrid images of your choosing (feel free to take inspirations from this page).

Hints

- use `torchvision.transforms.functional.gaussian_blur`
- You may have to run multiple times to get a really good result for the same reasons as above



Hybrid image of a skull and a waterfall

▼ Bells & Whistles (Optional)

- **More visual anagrams!** Visual anagrams in part 1.8 are created by flipping images upside down. However, there are much more transformations that also create visual anagrams! Refer to this paper and select two more transformations to create visual anagrams.
- **Design a course logo**! Doing text-conditioned image-to-image translation on UCB's logo or your drawing may be a good idea.
- **Your own ideas**: Be creative!

▼ Deliverable Checklist

- Make sure that your website and submission include **all the deliverables** in each section above.
- Submit your **PDF** and **code** to corresponding assignments on Gradescope.

▼ Acknowledgements

This project was a joint effort by Daniel Geng, Ryan Tabrizi, Hang Gao, Jingfeng Yang, and Jameson Crate, advised by Liyue Shen, Andrew Owens, and Alexei Efros.

</details>