
A. COMBI MONOBLOCK (≤22 m³ — Press & Container Joined as One Unit)
DIN Hook
[S3] SMART PLC + IMU
Honeywell TARS-IMU (±0.3°)
PRESS HEAD
Ram 35–40t
JOINED CONTAINER (Up to 22 m³)
C.o.G. Shifts Rearward (0.35L → 0.62L)
Gravity Vector (Slope Compensated)
[S1] 2× Front Elastomer Pucks (10t)
[S2] 2× Flintec CC1 Ø45mm Pins (10t)
Bay Slope θ (1°–4°) Compensated by IMU
Weight Calculation: Front Support Force + Rear Axle Force (Corrected for Ground Slope)
B. DUO STATIONARY PRESS + DETACHABLE CONTAINER (≤30 m³ — 0 Wires on Box!)
[S3] ON-SITE PLC+IMU
100% Wiring Stays Here
STATIONARY
DUO PRESS
Bolted to Concrete
SWAPPED DUMB CONTAINER (Up to 30 m³)
Zero Sensors, Zero Batteries, Zero Cables on Swapped Container
[S5] 2× Flintec SB4 Rail Pads (10t)
[S4] 2× Flintec CC1 Hook Clevis Pins (10t): Captures 15–30% Clamp Load
DUO Weight Calculation: Press Locking Hook Force + Rear Wheel Pad Force (Zero Box Wires)