

# *systemPipeR*: utilities for building NGS analysis pipelines

Thomas Girke  
Email contact: [thomas.girke@ucr.edu](mailto:thomas.girke@ucr.edu)

June 21, 2014

## 1 Introduction

---

*systemPipeR* is a pipeline for running command-line software, such as NGS aligners, on both single machines or compute clusters. It supports both interactive job submissions or batch submissions to queuing systems of clusters (tested only with Torque). *systemPipeR* can be used with most command-line aligners such as TopHat 2 (Kim et al., 2013) and Bowtie 2 (Langmead and Salzberg, 2012).

## Contents

---

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>Getting Started</b>	<b>2</b>
2.1	Installation . . . . .	2
2.2	Loading the Package and Documentation . . . . .	2
2.3	Sample FASTQ Files . . . . .	2
<b>3</b>	<b>Structure of targets file</b>	<b>2</b>
<b>4</b>	<b>Structure of param file and SYSargs container</b>	<b>3</b>
<b>5</b>	<b>Workflow</b>	<b>4</b>
5.1	Define environment settings and samples . . . . .	4
5.2	Alignment with Tophat 2 . . . . .	4
5.3	Create symbolic links for viewing BAM files in IGV . . . . .	5
5.4	Alignment with Bowtie 2 (here for miRNA profiling experiment) . . . . .	5
5.5	Read counting for mRNA profiling experiments . . . . .	5
5.6	Read counting for miRNA profiling experiments . . . . .	5
5.7	Correlation analysis of samples . . . . .	6
5.8	DEG analysis with <i>edgeR</i> . . . . .	6
<b>6</b>	<b>Version Information</b>	<b>7</b>
<b>7</b>	<b>Funding</b>	<b>7</b>
<b>8</b>	<b>References</b>	<b>7</b>

## 2 Getting Started

---

### 2.1 Installation

The R software can be downloaded from CRAN (<http://cran.at.r-project.org/>) and the *systemPipeR* package from GitHub (<https://github.com/tgirke/systemPipeR>). The *systemPipeR* package can be installed from R using the `install.packages` command after downloading and uncompressing the package directory.

```
> system("R CMD build systemPipeR") # Builds package
> install.packages("systemPipeR.X.X.X.tar.gz", repos=NULL, type="source") # Installs the package
```

### 2.2 Loading the Package and Documentation

```
> library("systemPipeR") # Loads the package
> library(help="systemPipeR") # Lists all functions and classes
> vignette("systemPipeR") # Opens this PDF manual from R
```

### 2.3 Sample FASTQ Files

Mini sample FASTQ files used by this overview vignette as well as the associated workflow reporting vignettes can be downloaded from [here](#). This data set contains 18 paired-end (PE) read sets from *Arabidopsis thaliana* published by (Howard et al., 2013, [SRA: SRP010938](#)). To minimize processing time during testing, each FASTQ file has been subsetting to 90,000-10,000 random sampled PE reads that map to the first 100,000 nucleotides of each chromosome of the *A. thaliana* genome. The corresponding reference genome sequence (FASTA) and its GFF annotation files (also provided in the downloadable archive) have been truncated accordingly. This way the entire test sample data set is less than 200MB in storage space. A PE read set has been chosen for this test data set for flexibility, because it can be used for testing both types of analysis routines requiring either SE (single end) reads or PE reads.

## 3 Structure of targets file

---

The targets file defines all FASTQ files and sample comparisons of an analysis workflow. The following shows the format of a sample targets file provided by this package.

```
> library(systemPipeR)
> targetspath <- paste0(system.file("extdata", package="systemPipeR"), "/targets.txt")
> read.delim(targetspath, comment.char = "#")
```

	FileName	SampleName	Factor	SampleLong	Experiment	Date
1	./data/SRR446027_1.fastq	M1A	M1	Mock.1h.A	1	23-Mar-2012
2	./data/SRR446028_1.fastq	M1B	M1	Mock.1h.B	1	23-Mar-2012
3	./data/SRR446029_1.fastq	A1A	A1	Avr.1h.A	1	23-Mar-2012
4	./data/SRR446030_1.fastq	A1B	A1	Avr.1h.B	1	23-Mar-2012
5	./data/SRR446031_1.fastq	V1A	V1	Vir.1h.A	1	23-Mar-2012
6	./data/SRR446032_1.fastq	V1B	V1	Vir.1h.B	1	23-Mar-2012
7	./data/SRR446033_1.fastq	M6A	M6	Mock.6h.A	1	23-Mar-2012
8	./data/SRR446034_1.fastq	M6B	M6	Mock.6h.B	1	23-Mar-2012
9	./data/SRR446035_1.fastq	A6A	A6	Avr.6h.A	1	23-Mar-2012
10	./data/SRR446036_1.fastq	A6B	A6	Avr.6h.B	1	23-Mar-2012
11	./data/SRR446037_1.fastq	V6A	V6	Vir.6h.A	1	23-Mar-2012
12	./data/SRR446038_1.fastq	V6B	V6	Vir.6h.B	1	23-Mar-2012
13	./data/SRR446039_1.fastq	M12A	M12	Mock.12h.A	1	23-Mar-2012
14	./data/SRR446040_1.fastq	M12B	M12	Mock.12h.B	1	23-Mar-2012
15	./data/SRR446041_1.fastq	A12A	A12	Avr.12h.A	1	23-Mar-2012
16	./data/SRR446042_1.fastq	A12B	A12	Avr.12h.B	1	23-Mar-2012
17	./data/SRR446043_1.fastq	V12A	V12	Vir.12h.A	1	23-Mar-2012
18	./data/SRR446044_1.fastq	V12B	V12	Vir.12h.B	1	23-Mar-2012

Structure of targets file for paired end (PE) samples.

```
> library(systemPipeR)
> targetspath <- paste0(system.file("extdata", package="systemPipeR"), "/targetsPE.txt")
> read.delim(targetspath, comment.char = "#")[1:2,1:6]
```

	FileName1	FileName2	SampleName	Factor	SampleLong	Experiment
1	./data/SRR446027_1.fastq	./data/SRR446027_2.fastq	M1A	M1	Mock.1h.A	1
2	./data/SRR446028_1.fastq	./data/SRR446028_2.fastq	M1B	M1	Mock.1h.B	1

Comparisons are defined in the header lines of the targets starting with '# <CMP>'. The function readComp imports the comparison and stores them in a list.

```
> readComp(file=targetspath, format="vector", delim="-")
```

```
$CMPset1
[1] "M1-A1" "M1-V1" "A1-V1" "M6-A6" "M6-V6" "A6-V6" "M12-A12" "M12-V12" "A12-V12"
```

```
$CMPset2
[1] "M1-A1" "M1-V1" "M1-M6" "M1-A6" "M1-V6" "M1-M12" "M1-A12" "M1-V12" "A1-V1"
[10] "A1-M6" "A1-A6" "A1-V6" "A1-M12" "A1-A12" "A1-V12" "V1-M6" "V1-A6" "V1-V6"
[19] "V1-M12" "V1-A12" "V1-V12" "M6-A6" "M6-V6" "M6-M12" "M6-A12" "M6-V12" "A6-V6"
[28] "A6-M12" "A6-A12" "A6-V12" "V6-M12" "V6-A12" "V6-V12" "M12-A12" "M12-V12" "A12-V12"
```

## 4 Structure of param file and SYSargs container

The param file defines the parameters of the command-line software. The following shows the format of a sample param file provided by this package.

```
> parampath <- paste0(system.file("extdata", package="systemPipeR"), "/tophat.param")
> read.delim(parampath, comment.char = "#")
```

	PairSet	Name	Value
1	modules	<NA>	bowtie2/2.1.0
2	modules	<NA>	tophat/2.0.8b
3	software	<NA>	tophat
4	cores	-p	4
5	other	<NA>	-g 1 --segment-length 25 -i 30 -I 3000
6	outfile1	-o	<FileName1>
7	outfile1	path	./results/
8	outfile1	remove	<NA>
9	outfile1	append	.tophat
10	outfile1	outextension	.tophat/accepted_hits.bam
11	reference	<NA>	./data/tair10.fasta
12	infile1	<NA>	<FileName1>
13	infile1	path	<NA>
14	infile2	<NA>	<FileName2>
15	infile2	path	<NA>

The systemArgs function imports the definitions of both the param file and the targets file, and stores all relevant information as SYSargs object.

```
> args <- systemArgs(sysma=parampath, mytargets=targetspath)
> args
```

An instance of 'SYSargs' for running 'tophat' on 18 samples

Several accessor functions are available that are named after the slot names of the SYSargs object class.

```
> names(args)
[1] "modules" "software" "cores" "other" "reference" "results" "infile1"
[8] "infile2" "outfile1" "sysargs" "outpaths"
```

```
> modules(args)
```

```
[1] "bowtie2/2.1.0" "tophat/2.0.8b"
```

```
> cores(args)
```

```
[1] 4
```

```
> outpaths(args)[1]
```

```
M1A
"/rhome/tgirke/Projects/github/systemPipeR/vignettes/results/SRR446027_1.fastq.tophat/accepted_hits.bam"
```

```
> sysargs(args)[1]
```

```
"tophat -p 4 -g 1 --segment-length 25 -i 30 -I 3000 -o /rhome/tgirke/Projects/github/systemPipeR/vignettes,
```

The content of the param file can be returned as JSON object as follows (requires *rjson* package).

```
> systemArgs(sysma=parampath, mytargets=targetspath, type="json")
```

```
[1] "{\"modules\":{\"n1\":\"\", \"v2\":\"bowtie2/2.1.0\", \"n1\":\"\", \"v2\":\"tophat/2.0.8b\"}, \"software\""
```

## 5 Workflow

### 5.1 Define environment settings and samples

Load package:

```
> library(systemPipeR)
```

Subset input targets file as needed. Note: for qsubRun the targets file needs to contain absolute paths to FASTQ files in the 'FileName' column.

```
> targets <- read.delim(targetspath, comment.char = "#")
```

```
> write.table(targets, "targets_run.txt", row.names=FALSE, quote=FALSE, sep="\t")
```

Construct SYSargs object from param and targets files.

```
> args <- systemArgs(sysma=parampath, mytargets="targets_run.txt")
```

### 5.2 Alignment with Tophat 2

Build Bowtie 2 index.

```
> system("bowtie2-build ./data/mygenome.fa ./data/bowtie2index/mygenome")
```

Execute SYSargs on a single machine without submitting to a queuing system of a compute cluster.

```
> bampaths <- runCommandline(args=args)
```

Submit to compute nodes.

```
> qsubargs <- getQsubargs(queue="batch", Nnodes="nodes=1", cores=cores(args), memory="mem=10gb", time="wal.
```

```
> (joblist <- qsubRun(args=args, qsubargs=qsubargs, Nqsubs=4, package="systemPipeR"))
```

Alignment Stats

```
> read_statsDF <- alignStats(args, fqgz=TRUE)
```

```
> read_statsDF <- cbind(read_statsDF[targets$FileName,], targets)
```

```
> write.table(read_statsDF, "results/alignStats.xls", row.names=FALSE, quote=FALSE, sep="\t")
```

### 5.3 Create symbolic links for viewing BAM files in IGV

```
> symLink2bam(sysargs=args, htldir=c("~/html/", "somedir/"),
+            urlbase="http://myserver.edu/~username/",
+            urlfile="IGVurl.txt")
```

### 5.4 Alignment with Bowtie 2 (here for miRNA profiling experiment)

Run as single process without submitting to cluster, e.g. via qsub -l.

```
> parampath <- paste0(system.file("extdata", package="systemPipeR"), "/bowtieSE.param")
> args <- systemArgs(sysma=parampath, mytargets="targets_run.txt")
> bampaths <- runCommandline(args=args)
```

Submit to compute nodes

```
> qsubargs <- getQsubargs(queue="batch", Nnodes="nodes=1", cores=cores(args), memory="mem=10gb", time="walltime=1000")
> (joblist <- qsubRun(args=args, qsubargs=qsubargs, Nqsubs=4, package="systemPipeR"))
```

### 5.5 Read counting for mRNA profiling experiments

Create txdb (do only once)

```
> txdb <- makeTranscriptDbFromGFF(file="data/mygenome.gtf", format="gtf", dataSource="ENSEMBL", species="MySpecies")
> saveDb(txdb, file="./data/My_species.sqlite")
```

Read counting with summarizeOverlaps in parallel mode with multiple cores

```
> library(BiocParallel)
> txdb <- loadDb("./data/My_species.sqlite")
> eByg <- exonsBy(txdb, by="gene")
> bams <- names(bampaths); names(bams) <- targets$SampleName
> bfl <- BamFileList(bams, yieldSize=50000, index=character())
> multicoreParam <- MulticoreParam(workers=4); register(multicoreParam); registered()
> counteByg <- bplapply(bfl, function(x) summarizeOverlaps(gff, x, mode="Union", ignore.strand=TRUE, inter.feature=FALSE))
> countDFeByg <- sapply(seq(along=counteByg), function(x) assays(counteByg[[x]])$counts)
> rownames(countDFeByg) <- names(rowData(counteByg[[1]])); colnames(countDFeByg) <- names(bfl)
> rpkmDFeByg <- apply(countDFeByg, 2, function(x) returnRPKM(counts=x, gffsub=eByg))
> write.table(assays(countDFeByg)$counts, "results/countDFeByg.xls", col.names=NA, quote=FALSE, sep="\t")
> write.table(rpkmDFeByg, "results/rpkmDFeByg.xls", col.names=NA, quote=FALSE, sep="\t")
```

### 5.6 Read counting for miRNA profiling experiments

Download miRNA genes from miRBase

```
> system("wget ftp://mirbase.org/pub/mirbase/19/genomes/My_species.gff3 -P ./data/")
> gff <- import.gff("./data/My_species.gff3", asRangedData=FALSE)
> gff <- split(gff, elementMetadata(gff)$ID)
> bams <- names(bampaths); names(bams) <- targets$SampleName
> bfl <- BamFileList(bams, yieldSize=50000, index=character())
> countDFmiR <- summarizeOverlaps(gff, bfl, mode="Union", ignore.strand=FALSE, inter.feature=FALSE) # Note
> rpkmDFmiR <- apply(countDFmiR, 2, function(x) returnRPKM(counts=x, gffsub=gff))
> write.table(assays(countDFmiR)$counts, "results/countDFmiR.xls", col.names=NA, quote=FALSE, sep="\t")
> write.table(rpkmDFmiR, "results/rpkmDFmiR.xls", col.names=NA, quote=FALSE, sep="\t")
```

## 5.7 Correlation analysis of samples

```
> library(ape)
> rpkmDFeByg <- read.table("./results/rpkmDFeByg.xls", check.names=FALSE)
> rpkmDFeByg <- rpkmDFeByg[rowMeans(rpkmDFeByg) > 50,]
> d <- cor(rpkmDFeByg, method="spearman")
> hc <- hclust(as.dist(1-d))
> plot.phylo(as.phylo(hc), type="p", edge.col="blue", edge.width=2, show.node.label=TRUE, no.margin=TRUE)
```

## 5.8 DEG analysis with edgeR

```
> targetspath <- paste0(system.file("extdata", package="systemPipeR"), "/targets.txt")
> targets <- read.delim(targetspath, comment.char = "#")
> (cmp <- readComp(file=targetspath, format="matrix", delim="-"))
```

\$CMPset1

	[,1]	[,2]
[1,]	"M1"	"A1"
[2,]	"M1"	"V1"
[3,]	"A1"	"V1"
[4,]	"M6"	"A6"
[5,]	"M6"	"V6"
[6,]	"A6"	"V6"
[7,]	"M12"	"A12"
[8,]	"M12"	"V12"
[9,]	"A12"	"V12"

\$CMPset2

	[,1]	[,2]
[1,]	"M1"	"A1"
[2,]	"M1"	"V1"
[3,]	"M1"	"M6"
[4,]	"M1"	"A6"
[5,]	"M1"	"V6"
[6,]	"M1"	"M12"
[7,]	"M1"	"A12"
[8,]	"M1"	"V12"
[9,]	"A1"	"V1"
[10,]	"A1"	"M6"
[11,]	"A1"	"A6"
[12,]	"A1"	"V6"
[13,]	"A1"	"M12"
[14,]	"A1"	"A12"
[15,]	"A1"	"V12"
[16,]	"V1"	"M6"
[17,]	"V1"	"A6"
[18,]	"V1"	"V6"
[19,]	"V1"	"M12"
[20,]	"V1"	"A12"
[21,]	"V1"	"V12"
[22,]	"M6"	"A6"
[23,]	"M6"	"V6"
[24,]	"M6"	"M12"
[25,]	"M6"	"A12"
[26,]	"M6"	"V12"

```
[27,] "A6" "V6"
[28,] "A6" "M12"
[29,] "A6" "A12"
[30,] "A6" "V12"
[31,] "V6" "M12"
[32,] "V6" "A12"
[33,] "V6" "V12"
[34,] "M12" "A12"
[35,] "M12" "V12"
[36,] "A12" "V12"
```

```
> edgeDF <- run_edgeR(countDF=countDF, targets=targets, cmp=cmp[[1]], independent=TRUE, mdsplot="")
```

## 6 Version Information

---

```
> toLatex(sessionInfo())
```

- R version 3.0.2 (2013-09-25), x86\_64-unknown-linux-gnu
- Locale: C
- Base packages: base, datasets, grDevices, graphics, methods, parallel, stats, utils
- Other packages: BiocGenerics 0.8.0, Biostrings 2.30.1, GenomicRanges 1.14.2, IRanges 1.20.1, Rsamtools 1.14.2, ShortRead 1.20.0, XVector 0.2.0, edgeR 3.4.2, lattice 0.20-24, limma 3.18.11, rjson 0.2.13, systemPipeR 1.0.7
- Loaded via a namespace (and not attached): Biobase 2.22.0, BiocStyle 1.0.0, RColorBrewer 1.0-5, bitops 1.0-6, grid 3.0.2, hwriter 1.3, latticeExtra 0.6-26, stats4 3.0.2, tools 3.0.2, zlibbioc 1.8.0

## 7 Funding

---

This software was developed with funding from the National Science Foundation: [MCB-1021969](#) .

## 8 References

---

- Brian E Howard, Qiwen Hu, Ahmet Can Babaoglu, Manan Chandra, Monica Borghi, Xiaoping Tan, Luyan He, Heike Winter-Sederoff, Walter Gassmann, Paola Veronese, and Steffen Heber. High-throughput RNA sequencing of pseudomonas-infected arabidopsis reveals hidden transcriptome complexity and novel splice variants. *PLoS One*, 8(10):e74183, 1 October 2013. ISSN 1932-6203. doi: 10.1371/journal.pone.0074183. URL <http://dx.doi.org/10.1371/journal.pone.0074183>.
- Daehwan Kim, Geo Pertea, Cole Trapnell, Harold Pimentel, Ryan Kelley, and Steven L Salzberg. TopHat2: accurate alignment of transcriptomes in the presence of insertions, deletions and gene fusions. *Genome Biol.*, 14(4):R36, 25 April 2013. ISSN 1465-6906. doi: 10.1186/gb-2013-14-4-r36. URL <http://dx.doi.org/10.1186/gb-2013-14-4-r36>.
- Ben Langmead and Steven L Salzberg. Fast gapped-read alignment with bowtie 2. *Nat. Methods*, 9(4):357–359, April 2012. ISSN 1548-7091. doi: 10.1038/nmeth.1923. URL <http://dx.doi.org/10.1038/nmeth.1923>.