jt_address

🔑 addr_id	integer(11)	U
address	varchar(255)	N
city	varchar(255)	N
state	varchar(255)	N
zip	varchar(255)	N

jt_loc

🔑 loc_id	integer(11)	U
x_coord	integer(11)	
y_coord	integer(11)	
addr_id	integer(11)	

Address

Location

jt_passenger

🔑 pass_id	integer(11)	U
jag_number	varchar(20)	N
email	varchar(100)	N
first_name	varchar(150)	N
last_name	varchar(150)	N
departure_stop_id	integer(11)	
arrival_stop_id	integer(11)	
current_bus_id	integer(11)	
Column	integer(10)	N

jt_stop

🔑 stop_id	integer(11)	U
stop_num	integer(11)	N
loc_id	integer(11)	

departing stop

destination stop

jt_route_stop

🔑 link_id	integer(11)	U
route_id	integer(11)	
stop_id	integer(11)	
next_stop_id	integer(11)	
avg_time_to_next_stop	float(11)	
distance_to_next_stop	integer(11)	N

referenced stop

next stop in route

current bus passenger is on

stop info is about this route

jt_bus

🔑 bus_id	integer(11)	U
max_seats	integer(11)	N
arrival_time	timestamp	N
departure_time	timestamp	N
current_route_id	integer(11)	
current_loc_id	integer(1)	N
next_stop_id	integer(11)	
passenger_count	integer(11)	N

bus to route

jt_route_bus

🔑 link_id	integer(11)	
route_id	integer(11)	
bus_id	integer(11)	

jt_route

🔑 route_id	integer(11)	
color	varchar(20)	N
start_time	timestamp	N
end_time	timestamp	N